

NORTHWEST CORNER SECTION 30, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 94 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE CORNER TO SECTIONS 19 AND 30, TOWNSHIP 17, RANGE 13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 29, 1855.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE **MULBERRY POST** THAT THEY SET FOR THE WEST QUARTER CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13.
 - 2) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 12" X 3-1/2" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 30 AND 31, TOWNSHIP 17, RANGE 13.
 - 3) 40.00 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THAT THEY SET FOR THE QUARTER CORNER BETWEEN SECTIONS 19 AND 30, TOWNSHIP 17, RANGE 13.
 - 4) 41.42 CHAINS EAST TO THE 18" X 10" X 3" LIMESTONE THAT THEY SET ON THE WEST BOUNDARY OF THE SAC AND FOX RESERVATION LANDS.
 - 5) 79.72 CHAINS EAST TO THE 22" X 14" X 3-1/2" SANDSTONE THAT THEY SET FOR THE CORNER TO SECTIONS 18, 20, 29 AND 30, TOWNSHIP 17, RANGE 13.
- 2) H. S. SLEEPER, DEPUTY COUNTY SURVEYOR FOR G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 26 FOR THE *FOREST HILL TO WATERLOO ROAD* [PACKET 164 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED MARCH 15 AND 16, 1859.

HE APPARENTLY **FOUND** THE NORTHEAST CORNER OF SECTION 25, TOWNSHIP 17, RANGE 12 ON THE RANGE LINE ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE NORTHEAST CORNER OF SECTION 25, TOWNSHIP 17, RANGE 12 ON THE RANGE LINE WAS THE **GLO LIMESTONE 24" X 12" X 3"**.

HIS SURVEY NOTES AND *PLAT OF SURVEY* SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE NORTH QUARTER CORNER OF SECTION 12, TOWNSHIP 19, RANGE 12; THENCE NORTH THROUGH THE MIDDLE OF SECTION 1 [TOWNSHIP 19, RANGE 12 TO THE NORTH QUARTER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE BY HIS *PLAT OF SURVEY*]; THENCE NORTH 45° EAST 226 RODS 7 LINKS TO THE EAST QUARTER CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12; THENCE NORTH ON THE TOWNSHIP LINE OF RANGES 12 AND 13 TO THE NORTHEAST CORNER OF SECTION 13, TOWNSHIP 17, RANGE 12; THENCE NORTH 48 RODS, 20 LINKS; THENCE NORTH 25° EAST 30 RODS; THENCE NORTH 7° EAST 96 RODS TO THE SOUTH LINE OF *WATERLOO TOWN SITE*; THENCE NORTH TO *MICHEL'S HOTEL IN WATERLOO*.
 - 2) THE ROAD WAS ESTABLISHED ON APRIL 4, 1959.
 - 3) A NOTE IN **RED** IN THE LEFT MARGIN OF PAGE 26 STATES: **COMMISSIONER'S RECORD PAGE 59.**
 - 4) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY, SO BY THE TERRITORIAL LAW IN EFFECT IN CHAPTER 77, SECTION 66, APPROVED FEBRUARY 4, 1859, THE WIDTH WOULD BE FOUR RODS (66 FEET) WIDE.
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 22 RECORDED IN SURVEY BOOK "A" ON PAGE 118 FOR THE SURVEY OF W. JACOBY'S LAND, TO ESTABLISH THE CENTER CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13, AND TO DIVIDE THE NORTHWEST 1/4 OF SECTION 30, TOWNSHIP 17, RANGE 13 NORTH AND SOUTH, THAT HE SURVEYED ON MARCH 3, 1868.

HIS INFORMATION IS CONTINUED PAGE 2

HE SAID THAT **HE FOUND THE CORNER STONE** AT THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE ON THIS SURVEY.

HE DID NOT DESCRIBE THE **CORNER STONE** THAT HE FOUND AT THIS CONNER IN HIS FIELD NOTES ON THIS SURVEY, BUT THE MONUMENT OF RECORD FOR THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE WAS THE **GLO LIMESTONE 24" X 12" X 3"**.

HE NOTED THAT NO *PLAT OF SURVEY* WAS DESIRED FOR THIS SURVEY.

HIS FIELD NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 78 RODS, 6-1/4 LINKS EAST TO THE **DIVISION CORNER** THAT HE ESTABLISHED ON THIS SURVEY.
 - 2) 156 RODS, 17-1/2 LINKS EAST TO THE NORTH QUARTER CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13.
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER THIRTY-THREE OF THE 6TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 33 TO ESTABLISH SECTION AND QUARTER SECTION CORNERS ON THE RANGE LINE BETWEEN RANGES 12 AND 13 IN TOWNSHIP 17, THAT HE SURVEYED ON MAY 16 AND 17, 1870.

HE SAID THAT SAID THAT **HE FOUND** THE CORNER TO SECTIONS 24, 25, 19 AND 30 ON THE RANGE LINE THIS **PERMANENT SURVEY ON THE RANGE LINE**.

HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER IN HIS FIELD NOTES ON THIS **PERMANENT SURVEY**, BUT THE MONUMENT OF RECORD FOR THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE WAS THE **GLO LIMESTONE 24" X 12" X 3"**.

THERE WAS NO *PLAT OF SURVEY* RECORDED FOR THIS **PERMANENT SURVEY ON THE RANGE LINE**.

HIS FIELD NOTES ARE AS FOLLOWS:

- 1) FROM THE QUARTER SECTION CORNER BETWEEN SECTIONS 25 AND 30, WHICH CORNER I ESTABLISHED BY WITNESS TREES FROM THE FIELD NOTES, BOTH TREES STANDING WITH THE MARKS QUITE DISTINCT ON THEM.
 - 2) FROM THE ABOVE DESCRIBED CORNER, I RAN NORTH VARIATION 11°20' EAST 2,649 FEET CAME TO THE CORNER TO SECTIONS 24, 25, 19 AND 30 FROM WHICH I FELL 9 FEET WEST, FROM WHICH I RAN NORTH VARIATION 11°15' EAST.
 - 3) AT EVERY 2,640 FEET SET TEMPORARY CORNER POSTS. AT 4 MILES AND 62 FEET CAME TO THE TOWNSHIP CORNER, FROM WHICH I FELL 50 FEET WEST. THE CORRECTION WILL THEREFOR BE 9 FEET EAST AND 3-1/3 (?) FEET NORTH, WHICH CORRECTION I MADE AND SET STONES FOR THE PERMANENT CORNERS ON THE RANGE LINE.
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE OF PAGE 232 FOR A COUNTY ROAD SURVEY IN TOWNSHIP 17, RANGE 13, THAT HE SURVEYED ON SEPTEMBER 3, 1881.

HE SAID THAT **HE FOUND** THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 19, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE SOUTHWEST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY WAS THE **GLO LIMESTONE 24" X 12" X 3"**.

HIS FIELD NOTES AND *PLAT OF SURVEY* SHOWS THE FOLLOWING INFORMATION:

THE INFORMATION IS CONTINUED PAGE 3

- 1) COMMENCING AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 19, TOWNSHIP 17, RANGE 13 [ON THE RANGE LINE], I RAN EAST VARIATION 10°15' 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13; THENCE EAST VARIATION 10°45' 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 20, TOWNSHIP 17, RANGE 13 [AT THE TERMINUS OF THIS ROAD SURVEY].
 - 2) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 147 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 174 TO 176 PETITIONED BY RILEY SANDERS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17, RANGE 13 [PACKET 386 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON SEPTEMBER 3, 1881.
- HE SAID THAT **HE FOUND** THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 19, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY.
- HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE SOUTHWEST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY WAS THE **GLO LIMESTONE 24" X 12" X 3"**.
- A NOTE ON THE PACKET COVER INDICATED THAT ROAD NUMBER 147 IS **RECORDED IN COMMISSIONERS' ROAD RECORD BOOK 2 ON PAGE 174.**
- HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) COMMENCING AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 19, TOWNSHIP 17, RANGE 13 [ON THE RANGE LINE], I RAN EAST VARIATION 10°15' 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13; THENCE EAST VARIATION 10°45' 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 20, TOWNSHIP 17, RANGE 13 [AT THE TERMINUS OF THIS ROAD SURVEY].
 - 2) THE VIEWERS REPORTED IN FAVOR OF LOCATING SAID ROAD AS BEING NECESSARY FOR PUBLIC USE.
 - 3) THE VIEWERS FURTHER DETERMINED THAT IF SAID ROAD BE LOCATED THAT ITS WIDTH SHALL BE 60 (SIXTY) FEET WIDE.
 - 4) THE ROAD WAS ESTABLISHED ON THE 5TH DAY OF OCTOBER 1881 AS ROAD NUMBER 147 AND THAT THE TRUSTEES OF READING TOWNSHIP BE NOTIFIED TO CAUSE THE SAME TO BE OPENED FOR PUBLIC TRAVEL.
 - 5) THE FINAL ORDER WAS SIGNED BY J. M. GRIFFITH, CHAIRMAN.
 - 6) ROAD NUMBER 147 WAS RECORDED ON THE 17TH DAY OF OCTOBER 1881 AND WAS ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK.
- 7) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY RECORDED IN VOLUME 429, PAGE 115 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 13, 1986, FOR THE SURVEY OF THREE TRACTS IN THE SOUTHEAST 1/4 OF SECTION 24, TOWNSHIP 17, RANGE 12 DATED OCTOBER 28, 1986, SURVEY F24001 IN THE SURVEY FILE FOR TOWNSHIP 17, RANGE 12, SAID THAT HE EXCAVATED WITH A LYON COUNTY ROAD GRADER OPERATED BY GLENN McANTEE OVER A WIDE AREA FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 25, TOWNSHIP 17, RANGE 12 ON THE RANGE LINE, BUT HE DID **NOT** FIND THE STONE.
- HE FOUND AN EXISTING 5/8" SQUARE IRON PIN THAT WAS 11.94 FEET EAST AND 7.87 FEET NORTH OF THE CORNER THAT **HE RE-ESTABLISHED** BY PROPORTIONATE MEASURE BETWEEN THE SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 17, RANGE 12 AND THE NORTHEAST CORNER OF SECTION 24, TOWNSHIP 17, RANGE 12.

HIS INFORMATION IS CONTINUED PAGE 4

HE SET A SQUARE 3/4" X 19" IRON BAR FOR THE NORTHEAST CORNER OF SECTION 25, TOWNSHIP 17, RANGE 12 ON THE RANGE LINE ON THIS SURVEY.

- 1) 10.0' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD TO THE EAST
- 2) 14.0' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD TO THE WEST
- 3) 7.0' EAST TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD TO THE NORTH
- 4) 42.0' NORTHEAST TO A SPIKE IN A CORNER FENCE POST
- 5) 42.1' EAST-SOUTHEAST TO A SPIKE IN A CORNER FENCE POST
- 6) **11.94' EAST AND 7.87' NORTH TO A 5/8" SQUARE IRON PIN FOUND AND NOT ACCEPTED**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,295.22' SOUTH ON THE RANGE LINE TO THE GLO STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 17, RANGE 12.
- 2) 687.40' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR THE NORTHEAST CORNER OF A 25.50 ACRE SURVEYED TRACT.
- 3) 2,647.61' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP THAT HE SET FOR THE EAST QUARTER CORNER OF SECTION 24, TOWNSHIP 17, RANGE 12.
- 4) 5,295.22' NORTH ON THE RANGE LINE TO THE GLO STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 24, TOWNSHIP 17, RANGE 12.

- 8) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 28, 1986, FOR HIS PROJECT NUMBER 86098, AND RECORDED IN VOLUME 429 ON PAGE 119 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 3, 1986, TO ESTABLISH THE EAST LINE OF THE WEST HALF OF THE WEST HALF OF THE SOUTHEAST 1/4 OF SECTION 25, TOWNSHIP 17, RANGE 12, SURVEY F25001 IN THE SURVEY FILE FOR TOWNSHIP 17, RANGE 12.

HE SAID THAT **HE FOUND THE EXISTING RECORD SQUARE 3/4" X 19" IRON PIN THAT HE HAD SET ON A PREVIOUS SURVEY AT THE NORTHEAST CORNER OF SECTION 25, TOWNSHIP 17, RANGE 12 ON THE RANGE LINE FROM HIS EXISTING REFERENCE TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.**

- 1) 10.0' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD TO THE EAST
- 2) 14.0' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD TO THE WEST
- 3) 7.0' EAST TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD TO THE NORTH
- 4) 42.0' NORTHEAST TO A SPIKE IN A CORNER FENCE POST
- 5) 42.1' EAST-SOUTHEAST TO A SPIKE IN A CORNER FENCE POST
- 6) **11.94' EAST AND 7.87' NORTH TO A 5/8" SQUARE IRON PIN FOUND AND NOT ACCEPTED**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,647.61' SOUTH ON THE RANGE LINE TO THE THEORETICAL POSITION FOR THE EAST 1/4 CORNER OF SECTION 25, TOWNSHIP 17, RANGE 12.
- 2) 5,295.22' SOUTH ON THE RANGE LINE TO THE GLO STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 17, RANGE 12.

- 9) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2017, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT **HE FOUND AND HE ACCEPTED THE EXISTING 5/8" SQUARE BAR** AT THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE PER CORNER TIE NOTES FILES BY STEVE BROSEMER, L.S. 752, FROM THE

LYON COUNTY ENGINEER'S OFFICE. HE ALSO FOUND THE EXISTING 5/8" SQUARE BAR AS REFERENCED HEREIN.

HE SENT THE FOLLOWING HORIZONTAL TIES:

1) **THIS RECOVERY REPORT HAS BEEN GENERATED PER KANSAS STATE REQUIREMENTS. SURVEY PREPARED HERewith IS ONGOING AND PART OF A LARGE PROJECT AND THUS THIS MONUMENTS POSITION HAS NOT YET BEEN FINALIZED AS THE TRUE CORNER LOCATION. SUBSEQUENT RECORD WILL BE FILED UPON COMPLETION OF THE ENTIRE SURVEY.**

- 2) 46.1' NORTH 36°19' EAST TO A SET 60 D NAIL IN THE TOP OF A CORNER POST
- 3) **14.3' NORTH 55°32' EAST TO A FOUND SQUARE 5/8" BAR.**
- 4) 43.9' NORTH 34°08' WEST TO THE FOUND FACE OF A 4" STEEL CORNER POST
- 5) 42.2' SOUTH 66°02' EAST TO THE FOUND FACE OF A 6" WOOD GATE POST

NOTE: IN HIS LAND SURVEY REFERENCE REPORT DATED OCTOBER 28, 1986, STEVEN S. BROSEMER HAD SET A 3/4" X 19" SQUARE IRON BAR FOR THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.

- 10) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 12, 2017, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT **HE FOUND AND HE ACCEPTED THE EXISTING 5/8" SQUARE BAR** AT THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE PER CORNER TIES NOTE FILED BY STEVE BROSEMER, LS 752, FROM THE LYON COUNTY ENGINEER'S OFFICE. HE ALSO FOUND THE EXISTING 5/8" SQUARE BAR AS REFERENCED HEREIN.

HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 46.1' NORTH 36°19' EAST TO A SET 60 D NAIL IN THE TOP OF A CORNER POST
- 2) **14.3' NORTH 55°32' EAST TO A FOUND SQUARE 5/8" BAR.**
- 3) 43.9' NORTH 34°08' WEST TO THE FOUND FACE OF A 4" STEEL CORNER POST
- 4) 42.2' SOUTH 66°02' EAST TO THE FOUND FACE OF A 6" WOOD GATE POST

NOTE: IN HIS LAND SURVEY REFERENCE REPORT DATED OCTOBER 28, 1986, STEVEN S. BROSEMER HAD SET A 3/4" X 19" SQUARE IRON BAR FOR THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.

- 11) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MAY 29, 2020, FOR THE DATE OF SURVEY MAY 1, 2020, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT **HE FOUND AND HE ACCEPTED THE EXISTING 5/8" SQUARE BAR** AT THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANE 13 PER THE CORNER TIE NOTES FILED BY STEVE BROSEMER, L.S. 752, FROM THE LYON COUNTY ENGINEER'S OFFICE. HE ALSO FOUND THE 5/8" SQUARE BAR AS REFERENCED HEREIN.

HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 46.1' NORTH 36°19' EAST TO A SET 60 D NAIL IN THE TOP OF A CORNER POST
- 2) **14.3' NORTH 55°32' EAST TO A FOUND SQUARE 5/8" BAR.**
- 3) 43.9' NORTH 34°08' WEST TO THE FOUND FACE OF A 4" STEEL CORNER POST
- 4) 42.2' SOUTH 66°02' EAST TO THE FOUND FACE OF A 6" WOOD GATE POST

NOTE: IN HIS LAND SURVEY REFERENCE REPORT DATED OCTOBER 28, 1986, STEVEN S. BROSEMER HAD SET A 3/4" X 19" SQUARE IRON BAR FOR THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.

CONTINUED PAGE 6

- 12) JOHN F. WATSON, P.S. 1587, OF SURVEYING AND MAPPING, L.L.C. FROM MIDLAND, TEXAS, IN A LAND SURVEY DATED NOVEMBER 29, 2021, FOR HIS PROJECT NUMBER 1021060678, WITH A DATE OF SURVEY OCTOBER 29, 2021, SAID THAT **HE FOUND AND HE ACCEPTED THE EXISTING 5/8" SQUARE BAR** AT THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE.

HE NOTED: FOUND AND ACCEPTED THE 5/8" SQUARE REBAR PER LAND SURVEY REFERENCE REPORTS 223090 AND 213031 (AT THE *KANSAS STATE HISTORICAL SOCIETY*) AND PER CORNER TIE NOTES FILED BY STEVE BROSEMER, L.S. 752, FROM THE LYON COUNTY ENGINEER'S OFFICE. ALSO FOUND THE 5/8" SQUARE REBAR AS REFERENCED HEREIN.

HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 46.1' NORTH 36°19' EAST TO A FOUND 60 D NAIL IN THE TOP OF A CORNER POST
- 2) **14.3' NORTH 55°32' EAST TO A FOUND SQUARE 5/8" BAR**
- 3) 43.9' NORTH 34°08' WEST TO THE FACE OF A 4" STEEL CORNER POST
- 4) 42.2' SOUTH 66°02' EAST TO THE FOUND FACE OF A 6" WOOD GATE POST

NOTE: IN HIS LAND SURVEY REFERENCE REPORT DATED OCTOBER 28, 1986, STEVEN S. BROSEMER HAD SET A **3/4" X 19" SQUARE IRON BAR** FOR THE NORTHWEST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13 ON THE RANGE LINE. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.

NORTHWEST CORNER 30-17-13