

INDIAN RESERVE CORNER ON NORTH LINE OF THE NORTHEAST QUARTER OF SECTION 31, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 628 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT AT 39.44 CHAINS WEST OF THE CORNER TO SECTIONS 29, 30, 31 & 32, TOWNSHIP 17, RANGE 13 THEY INTERSECTED THE WEST BOUNDARY OF THE SAC & FOX LANDS AT 22.48 CHAINS NORTH OF A STONE SET ON SAID LINE AND **THEY SET A LIMESTONE 22" X 12" X 2"** FOR THE CORNER TO FRACTIONAL SECTIONS 30 & 31, TOWNSHIP 17, RANGE 13 ON OCTOBER 14, 1860.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 0.70 CHAINS WEST TO THE 20" X 11" X 3" LIMESTONE THAT THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-17-13
 - 2) 40.70 CHAINS WEST TO THE 22" X 12" X 3-1/2" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 30 & 31-17-13 ON THE WEST TOWNSHIP BOUNDARY
 - 3) 39.44 CHAINS EAST TO THE 17" X 14" X 4" SANDSTONE THAT THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-17-13
- 2) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2017 FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT HE DEEMED THAT THE SAC & FOX RESERVE CORNER ON THE NORTH SIDE OF THE NORTHEAST 1/4 OF SECTION 31, TOWNSHIP 17, RANGE 13 WAS **OBLITERATED**. HE SET THIS CORNER BY SINGLE PROPORTION MEASUREMENT BETWEEN A FOUND STONE TO THE WEST AND A FOUND 5/8" REBAR FILED WITH AN ORANGE LYON COUNTY CAP TO THE EAST. **HE SET A 1/2" REBAR WITH A BLUE CAP "WATSON KS 1587"** FOR THE SAC & FOX INDIAN RESERVE CORNER ON THE NORTH SIDE OF THE NORTHEAST 1/4 CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13. HE SENT THE FOLLOWING **HORIZONTAL TIES:**

1) THIS RECOVERY REPORT HAS BEEN GENERATED PER KANSAS STATE REQUIREMENTS. SURVEY PREPARED HEREWITH IS ONGOING AND PART OF A LARGE PROJECT AND THUS THIS MONUMENTS POSITION HAS NOT YET BEEN FINALIZED AS THE TRUE CORNER LOCATION. SUBSEQUENT RECORD WILL BE FILED UPON COMPLETION OF THE ENTIRE SURVEY.

- 1) 50.8' S. 00°05' W. TO A SET 1/2" REBAR
- 2) 100.9' S. 00°05' W. TO A SET 1/2" REBAR
- 3) 150.1' S. 00°05' W. TO S SET 1/2" REBAR
- 4) 45.6' S. 88°25' W. TO A 1/2" REBAR SET FOR THE NORTH 1/4 CORNER OF SECTION 31-17-12

NOTE: HE DID NOT INDICATE IF HE EXCAVATED FOR THE STONE OF RECORD AT THIS CORNER, NOR DID HE HAVE THE COUNTY EXCAVATE FOR THE STONE. HE DEEMED THE CORNER OBLITERATED BUT HE APPARENTLY SET THIS CORNER AS A LOST CORNER. FUTURE SURVEYORS SHOULD EXCAVATE FOR THE STONE OF RECORD BEFORE ACCEPTING THIS REBAR FROM WATSON. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR

- 3) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 13, 2017 FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT HE EXCAVATED FOR THE ORIGINAL GLO STONE AT THE SAC & FOX RESERVE CORNER ON THE NORTH SIDE OF THE NORTHEAST 1/4 OF SECTION 31, TOWNSHIP 17, RANGE 13, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THE CORNER WAS **OBLITERATED**. HE SET THIS CORNER BY SINGLE PROPORTION MEASUREMENT BETWEEN A FOUND STONE TO THE WEST AND A FOUND 5/8" REBAR WITH A FILED ORANGE LYON COUNTY CAP TO THE EAST. HE SENT THE FOLLOWING **HORIZONTAL TIES:**

- 1) 50.8' S. 00°05' W. TO A SET 1/2" REBAR
- 2) 100.9' S. 00°05' W. TO A SET 1/2" REBAR
- 3) 150.1' S. 00°05' W. TO A SET 1/2" REBAR
- 4) 45.6' W. 88°25' W. TO A 1/2" REBAR HE SET FOR THE NORTH 1/4 CORNER OF SECTION 31-17-13

I R CORNER ON NORTH LINE NORTHEAST QUARTER 31-17-13