

WEST 1/4 CORNER OF SECTION 32, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 627 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 14" X 4"** FOR THE QUARTER CORNER BETWEEN SECTIONS 31 AND 32, TOWNSHIP 17, RANGE 13 ON OCTOBER 14, 1860.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 17" X 14" X 4" SANDSTONE THAT THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 AND 32, TOWNSHIP 17, RANGE 13.
- 2) 40.00 CHAINS SOUTH TO THE 22" X 12" X 3" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 31 AND 32, TOWNSHIP 17, RANGE 13 ON THE SOUTH TOWNSHIP BOUNDARY.
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 28 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 83 TO ESTABLISH THE CENTER CORNER, AND SUBDIVIDE THE NORTHEAST 1/4 INTO EAST 1/2, AND THE NORTHWEST 1/4 AND SOUTHWEST 1/4 OF SECTION 33, TOWNSHIP 17, RANGE 13, THAT HE SURVEYED ON JUNE 25, 1874.

HE SAID THAT **HE FOUND THE STONE** AT THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 ON THIS **PERMANENT SURVEY**.

HE DID NOT DESCRIBE THE STONE THAT HE FOUND AT THIS CORNER IN HIS FIELD NOTES ON THIS SURVEY, BUT THE STONE OF RECORD FOR THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS THE **GLO SANDSTONE 24" X 14" X 4"**.

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR A COUNTY ROAD IN TOWNSHIP 17, RANGE 13 RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE OF PAGE 158 THAT HE SURVEYED ON MAY 13, 1878.

HE SAID THAT **HE FOUND** THE QUARTER CORNER ON THE WEST LINE OF SECTION 32, TOWNSHIP 17, RANGE 13 ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS THE **GLO SANDSTONE 24" X 14" X 4"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13, I RAN WEST VARIATION 10°45' [ON THE 1/4 SECTION LINE FOR] 5,280 FEET TO THE QUARTER CORNER ON THE WEST LINE OF SECTION 32, TOWNSHIP 17, RANGE 13; THENCE WEST ON THE 1/4 SECTION LINE 5,280 FEET TO THE QUARTER CORNER ON THE WEST LINE OF SECTION 31, TOWNSHIP 17, RANGE 13 [ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY].
- 2) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE OF PAGE 192 FOR TWO (2) COUNTY ROADS IN TOWNSHIP 17, RANGE 13 THAT HE SURVEYED ON SEPTEMBER 3, 1880.

HE SAID THAT **HE FOUND** THE EAST QUARTER CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE EAST QUARTER CORNER OF SECTION 31,

TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY WAS THE **GLO SANDSTONE 24" X 14" X 4"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) THE FIRST ROAD: COMMENCING AT THE NORTHWEST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13 [ON THE RANGE LINE] I RAN EAST ON THE SECTION LINES 2 MILES TO THE NORTHEAST CORNER OF SECTION 20, TOWNSHIP 17, RANGE 13 [AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY].
- 2) THE SECOND ROAD: COMMENCING AT THE NORTHEAST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13, I RAN SOUTH 10°45' EAST 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13; THENCE SOUTH 10°30' EAST 2,406 FEET; THENCE SOUTH 64° EAST 257 FEET; THENCE SOUTH 30° WEST 55 FEET; THENCE NORTH 62° WEST 97 FEET; THENCE SOUTH 42° WEST 99 FEET; THENCE SOUTH 909 FEET; THENCE SOUTH 56° EAST 97 FEET; THENCE SOUTH 10°45' WEST 191 FEET; THENCE SOUTH ON THE SECTION LINE 1,530 FEET TO THE SECTION CORNER [SOUTHEAST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13]; THENCE SOUTH ON THE SECTION LINE 1,261 FEET; THENCE SOUTH 59°15' EAST 140 FEET; THENCE SOUTH 3°30' EAST 332 FEET; THENCE SOUTH 5° EAST 216 FEET; THENCE SOUTH ON THE EAST SIDE OF A STONE FENCE 730 FEET TO THE QUARTER CORNER [BETWEEN SECTIONS 31 AND 32, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY].
- 3) THERE WERE NO WIDTHS RECORDED FOR THE ROADS ON THIS ROAD SURVEY.
- 4) NOTE: HIS *PLAT OF SURVEY* SHOWS THAT THIS ROAD EXTENDS SOUTH OF THE TOWNSHIP LINE, HOWEVER, HIS *PLAT OF SURVEY* IN ROAD RECORD BOOK "A-1" ON 367 AND HIS *PLAT OF SURVEY* IN PACKET 217 SHOWS THAT THIS ROAD ENDS AT THE QUARTER CORNER BETWEEN SECTIONS 31 AND 32, TOWNSHIP 17, RANGE 13. WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR.

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 91 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 366 TO 368 PETITIONED BY THOMAS GERAGHTY AND OTHERS FOR TWO (2) COUNTY ROADS IN TOWNSHIP 17, RANGE 13 [PACKET 217 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 3, 1880.

HE SAID THAT **HE FOUND** THE EAST QUARTER CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE EAST QUARTER CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY WAS THE **GLO SANDSTONE 24" X 14" X 4"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) THE FIRST ROAD: COMMENCING AT THE NORTHWEST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13 [ON THE RANGE LINE] I RAN EAST ON THE SECTION LINES 2 MILES TO THE NORTHEAST CORNER OF SECTION 20, TOWNSHIP 17, RANGE 13 [AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY].
- 2) THE SECOND ROAD: COMMENCING AT THE NORTHEAST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13, I RAN SOUTH 10°45' EAST 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 19, TOWNSHIP 17, RANGE 13; THENCE SOUTH 10°30' EAST 2,406 FEET; THENCE SOUTH 64° EAST 257 FEET; THENCE SOUTH 30° WEST 55 FEET; THENCE NORTH 62° WEST 97 FEET; THENCE SOUTH 42° WEST 99 FEET; THENCE SOUTH 909 FEET; THENCE SOUTH 56° EAST 97 FEET; THENCE SOUTH 10°45' WEST 191 FEET; THENCE SOUTH ON THE SECTION LINE 1,530 FEET TO THE SECTION CORNER [SOUTHEAST CORNER OF SECTION 30, TOWNSHIP 17, RANGE 13]; THENCE SOUTH ON THE SECTION LINE 1,261 FEET; THENCE SOUTH 59°15' EAST 140 FEET; THENCE SOUTH 3°30' EAST 332 FEET; THENCE SOUTH 5°

EAST 216 FEET; THENCE SOUTH ON THE EAST SIDE OF A STONE FENCE 730 FEET TO THE QUARTER CORNER [BETWEEN SECTIONS 31 AND 32, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY].

- 3) THE VIEWERS REPORTED IN FAVOR OF LOCATING SAID ROAD AS BEING NECESSARY FOR PUBLIC TRAVEL.
 - 4) THE VIEWERS FURTHER DETERMINED THAT IF SAID ROAD BE LOCATED THAT ITS WIDTH SHALL BE FIFTY (50) FEET.
 - 5) THE ROADS WERE ESTABLISHED ON THE 13TH DAY OF OCTOBER 1880 AS ROAD NUMBER 91 AND THE TRUSTEES OF READING TOWNSHIP BE NOTIFIED TO CAUSE THE SAME TO BE OPENED FOR PUBLIC TRAVEL.
 - 6) THE FINAL ORDER WAS SIGNED BY I. A. TAYLOR, CHAIRMAN.
 - 7) ROAD NUMBER 91 WAS RECORDED ON THE 16TH DAY OF NOVEMBER 1880 AND WAS ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK.
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE OF PAGE 236 FOR A COUNTY ROAD SURVEY IN TOWNSHIP 17, RANGE 13 THAT HE SURVEYED ON JANUARY 2, 1882.

HE SAID THAT **HE FOUND** THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 TO COMMENCE THE ROAD LOCATED ON THIS ROAD SURVEY AND AT THE TERMINUS OF THE ROAD PETITIONED TO BE VACATED ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THIS ROAD SURVEY WAS THE **GLO SANDSTONE 24" X 14" X 4"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13; THENCE SOUTH 10°45' EAST 2,640 FEET TO THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 [AT THE TERMINUS OF THIS ROAD SURVEY].
 - 2) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.
 - 3) HE NOTED ON HIS *PLAT OF SURVEY* THAT THE ROAD FROM THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 EXTENDING EAST ONE MILE TO THE EAST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS TO BE VACATED BUT HE DID NOT SO STATE IN HIS FIELD NOTES.
- 7) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 152 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 194 TO 196 PETITIONED BY WILLIAM GERAGHTY AND OTHERS FOR THE LOCATION AND VACATION OF A COUNTY ROAD IN SECTION 32, TOWNSHIP 17, RANGE 13 [PACKET 440 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JANUARY 2, 1882.

HE SAID THAT **HE FOUND** THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THE ROAD LOCATED ON THIS ROAD SURVEY AND AT THE TERMINUS OF THE ROAD PETITIONED TO BE VACATED ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THIS ROAD SURVEY WAS THE **GLO SANDSTONE 24" X 14" X 4"**.

HIS INFORMATION IS CONTINUED PAGE 4

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13; THENCE SOUTH 10°45' EAST 2,640 FEET TO THE SOUTHWEST CORNER OF THE SOUTHWEST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 [ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY]
- 2) **THE ROAD PETITIONED TO BE VACATED:** COMMENCING AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13, THENCE WEST TO THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SAID SECTION 32, TOWNSHIP 17, RANGE 13.
- 3) THE VIEWERS REPORTED IN FAVOR OF LOCATING THE ROAD AS BEING NECESSARY FOR PUBLIC USE,
- 4) THE VIEWERS FURTHER RECOMMENDED **VACATING** ALL THAT PORTION OF THE ROAD AS PRAYED FOR IN THE PETITION **EXCEPT 3 RODS OFF THE WEST END OF SAID ROAD**
- 5) THE VIEWERS FURTHER DETERMINED THAT IF SAID ROAD BE LOCATED THAT ITS WIDTH SHALL BE **FIFTY (50) FEET**.
- 6) THE ROAD WAS ESTABLISHED ON THE 5TH DAY OF JANUARY 1882 AS ROAD NUMBER 152 AND THAT THE TRUSTEES OF READING TOWNSHIP BE NOTIFIED TO CAUSE THE SAME TO BE OPENED FOR PUBLIC TRAVEL.
- 7) THE FINAL ORDER WAS SIGNED BY J. M. GRIFFITH, CHAIRMAN.
- 8) ROAD NUMBER 152 WAS RECORDED ON THE 12TH DAY OF JANUARY 1882 AND WAS ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK.

- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER FIFTY-EIGHT, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 58 AT THE REQUEST OF ED YOUNGHAM TO **VACATE** A COUNTY ROAD IN SECTION 31, TOWNSHIP 17, RANGE 13, THAT HE SURVEYED ON AUGUST 25, 1884.

HE SAID THAT **HE FOUND** THE EAST QUARTER CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THIS ROAD **VACATION** SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD **VACATION** SURVEY, BUT THE MONUMENT OF RECORD FOR THE EAST QUARTER CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13 WAS THE **GLO SANDSTONE 24" X 14" X 4"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) BEGINNING AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 31, TOWNSHIP 17, RANGE 13; THENCE EAST ON THE 1/4 LINE ONE MILE TO THE EAST QUARTER CORNER OF SAID SECTION 31, TOWNSHIP 17, RANGE 13 [AT THE TERMINUS OF THIS ROAD **VACATION** SURVEY].

- 9) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 58, A ROAD SURVEY FOR ROAD NUMBER 286 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 94 TO 96 [PACKET 557 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] PETITIONED BY ED YOUNGHAM AND OTHERS FOR THE **VACATION** OF A COUNTY ROAD IN SECTION 31, TOWNSHIP 17, RANGE 13 THAT HE SURVEYED ON AUGUST 25, 1884.

HE SAID THAT **HE FOUND** THE EAST QUARTER CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THIS ROAD **VACATION** SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD **VACATION** SURVEY, BUT THE MONUMENT OF RECORD FOR THE EAST QUARTER CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13 WAS THE **GLO SANDSTONE 24" X 14" X 4"**.

A NOTE ON THE PACKET COVER SAID: SEE COMMISSIONERS' RECORD NUMBER 4 ON PAGE 155.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED PAGE 5

- 1) BEGINNING AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 31, TOWNSHIP 17, RANGE 13 [ON THE RANGE LINE]; THENCE EAST ON THE 1/4 LINE ONE MILE TO THE EAST QUARTER CORNER OF SAID SECTION 31, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THIS ROAD VACATION SURVEY.
 - 2) THE VIEWERS REPORTED IN FAVOR OF VACATING SAID ROAD FOR THE FOLLOWING REASONS, 1ST: PUBLIC TRAVEL DOES NOT REQUIRE THE USE OF SAID ROAD. THE MAIN TRAVELED ROAD IS A HALF MILE SOUTH AND IS THE ROAD LEADING FROM THE NORTH LINE OF READING TOWNSITE WEST TO THE *LAWRENCE AND EMPORIA STATE ROAD*. SAID ROAD TO BE VACATED HAS NEVER BEEN OPENED OR WORKED. 2ND: THE RESIDENT HOUSEHOLDS AFFECTED BY THIS VACATION HAVE LOCATED ROADS TO THE EAST, SOUTH, AND WEST SIDES OF SAID SECTION.
 - 3) THE ROAD WAS VACATED ON THE 9TH DAY OF JANUARY 1885 AND THAT THE TRUSTEES OF READING TOWNSHIP BE NOTIFIED TO CAUSE THE SAME TO BE VACATED FOR PUBLIC TRAVEL.
 - 4) THE FINAL ORDER WAS SIGNED BY P. Y. HALLBERG CHAIRMAN.
 - 5) THE ORDER WAS CERTIFIED AND RECORDED ON THE 24TH DAY OF MARCH 1885 AND WAS SIGNED BY ROLAND LAKIN, COUNTY CLERK.
 - 6) IT WAS NOTED ON PAGE 94: TRUSTEE NOTIFIED ON FEBRUARY 16, 1885.
- 10) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 4 IN THE COUNTY CLERK'S OFFICE:
ON SEPTEMBER 5, 1910, A PETITION SIGNED BY W. J. O'MARA AND 16 OTHERS FOR THE RELOCATION OF A ROAD IN TOWNSHIP 17, RANGE 13 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS.
- 1) THE ROAD WAS VIEWED ON OCTOBER 11, 1910, AND THE FINAL ORDER FOR THE RELOCATION OF THE FOLLOWING ROAD WAS ISSUED ON JANUARY 6, 1911.
 - 2) THE ROAD PETITIONED TO BE RELOCATED: COMMENCING AT THE SOUTHWEST CORNER OF THE NORTHWEST QUARTER OF SECTION 32, TOWNSHIP 17, RANGE 13, THENCE RUNNING NORTH UNTIL IT INTERSECTS THE ROAD ON THE SECTION LINE.
 - 3) THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ORDERED THAT THE ROAD BE RELOCATED AND ORDERED THE TRUSTEE OF READING TOWNSHIP TO OPEN THE ROAD TO A WIDTH OF 40 FEET.
- 11) J. MAX YINGLING, DEPUTY COUNTY SURVEYOR FOR J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY FOR ROAD NUMBER 660 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 17 [PACKET 793 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS PETITIONED BY W. J. O'MARA AND 16 OTHERS FOR A ROAD IN TOWNSHIP 17, RANGE 13.
- THE ROAD WAS VIEWED BY THE COUNTY COMMISSION AND THE COUNTY SURVEYOR ON OCTOBER 11, 1910.
- HE APPARENTLY **FOUND** THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THIS ROAD SURVEY.
- HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER AT THE TERMINUS OF THIS ROAD SURVEY IN HIS FIELD NOTES, BUT THE MONUMENT OF RECORD FOR THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS THE **GLO SANDSTONE 24" X 14" X 4"**.
- THERE WERE NO REFERENCE TIES TO THIS CORNER RECORDED ON THIS ROAD SURVEY.
- HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
HIS INFORMATION IS CONTINUED PAGE 6

- 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13, THENCE SOUTH 2,640 FEET TO THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SAID SECTION AND ENDING THERE.
 - 2) ROAD TO BE 40 FEET WIDE.
 - 3) IT WAS NOTED ON THE PACKET COVER THAT ROAD 660 WAS GRANTED ON THE 2ND DAY OF JANUARY 1911.
 - 4) A NOTE ON THE PACKET COVER SAID: THIS ROAD IS RECORDED IN COMMISSIONERS' ROAD JOURNAL A ON PAGE 4.
- 12) J. MAX YINGLING, DEPUTY COUNTY SURVEYOR FOR J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "D" PAGE 164 ON A PETITION BY W. J. O'MARA IN WHICH THE ROAD BEGINNING AT THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 AND RUNNING SOUTH ONE HALF MILE WAS STRAIGHTEN AND LAYED OUT ON THE SECTION LINE. HE NOTED THAT THIS SURVEY WAS ENTERED ON THE 5TH DAY OF JANUARY 1911.
- HE APPARENTLY **FOUND** THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 AT THE TERMINUS OF THIS ROAD SURVEY.
- HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER AT THE TERMINUS OF THIS ROAD SURVEY IN HIS FIELD NOTES, BUT THE MONUMENT OF RECORD FOR THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS THE **GLO SANDSTONE 24" X 14" X 4"**.
- THERE WERE NO REFERENCE TIES FOR THIS CORNER RECORDED ON THIS ROAD SURVEY.
- HIS FIELD NOTES ARE AS FOLLOWS:
- 1) BEGINNING AT THE STONE AT THE NORTHWEST CORNER OF SECTION 29, TOWNSHIP 17, RANGE 13, I RAN SOUTH ONE MILE TO THE NORTHWEST CORNER OF SECTION 32. TOWNSHIP 17, RANGE 13; THENCE SOUTH ONE-HALF MILE TO THE SOUTHWEST CORNER OF THE NORTHWEST QUARTER OF SECTION 32, TOWNSHIP 17, RANGE 13, CLEARLY MARKING THE CENTERLINE OF THE ROAD BY DRIVING STAKES AT FREQUENT INTERVALS.
 - 2) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY
- 13) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2017, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT HE DEEMED THAT THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS **OBLITERATED**.
- HE SET THIS CORNER BY SINGLE PROPORTION MEASUREMENT BETWEEN A FOUND 5/8" REBAR FILED WITH AN ORANGE LYON COUNTY CAP HALF-WAY TO THE NORTH AND A MAG NAIL WITH WASHER PROPERLY ESTABLISHED HALF WAY TO THE SOUTH.
- HE SET A 1/2" REBAR WITH BLUE CAP "WATSON KS 1587" FOR THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13.
- HE SENT THE FOLLOWING HORIZONTAL TIES:
- 1) **THIS RECOVERY REPORT HAS BEEN GENERATED PER KANSAS STATE REQUIREMENTS. SURVEY PREPARED HERewith IS ONGOING AND PART OF A LARGE PROJECT AND THUS THIS MONUMENTS POSITION HAS NOT YET BEEN FINALIZED AS THE TRUE CORNER LOCATION. SUBSEQUENT RECORD WILL BE FILED UPON COMPLETION OF THE ENTIRE SURVEY.**
 - 2) 35.1' NORTH 53°08' EAST TO THE FOUND FACE OF A 6" STEEL BRACE POST
 - 3) 31.2' NORTH 65°02' EAST TO A FOUND FACE OF A 6" STEEL CORNER POST
 - 4) 19.9' SOUTH 89°53' WEST TO A SET 3/8" REBAR
 - 5) 22.2' SOUTH 88°31' WEST TO A FOUND T-POST IN A NORTH AND SOUTH FENCE LINE

NOTE: HE DID NOT INDICATE IF HE EXCAVATED FOR THE STONE OF RECORD AT THIS CORNER, NOR DID HE HAVE THE COUNTY EXCAVATE FOR THE STONE. HE DEEMED THE CORNER OBLITERATED BUT HE “SET” THIS CORNER BY SINGLE PROPORTION MEASUREMENT AS A LOST CORNER. FUTURE SURVEYORS SHOULD EXCAVATE FOR THE STONE OF RECORD BEFORE ACCEPTING THIS REBAR FROM WATSON. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.

- 14) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 13, 2017, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT HE DEEMED THAT THE ORIGINAL STONE AT THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS **OBLITERATED** DUE TO THE ROAD CUT IN THE AREA.

HE SET THIS CORNER BY SINGLE PROPORTION MEASUREMENT BETWEEN A FOUND 5/8” REBAR FILED WITH AN ORANGE LYON COUNTY CAP HALF-WAY TO THE NORTH AND A MAG NAIL WITH WASHER PROPERLY ESTABLISHED HALF-WAY TO THE SOUTH.

HE SET A 1/2” REBAR WITH HIS BLUE “WATSON KS 1587” CAP FOR THE WEST QUARTER CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13.

HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 35.1’ NORTH 53°08’ EAST TO THE FOUND FACE OF A 6” STEEL BRACE POST
- 2) 31.2’ NORTH 65°02’ EAST TO THE FOUND FACE OF A 6” STEEL CORNER POST
- 3) 19.9’ SOUTH 89°53’ WEST TO A SET 3/8” REBAR
- 4) 22.2’ SOUTH 88°31’ WEST TO A FOUND T-POST IN A NORTH AND SOUTH FENCE LINE

NOTE: LYON COUNTY ENGINEERING TECHNICIAN MATT COLLINS WAS PRESENT WHEN THE SURVEY CREW FROM WATSON CAME BACK AND EXCAVATED WITH A LYON COUNTY GRADER FOR THE STONE AT THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 FOR LYON COUNTY PROJECT NUMBER 17-40 IN AUGUST 2017, BUT THEY DID **NOT** FIND THE STONE. MATT OBSERVED THAT THE SURVEY CREW THEN RESET THE ABOVE 1/2” REBAR WITH A BLUE “WATSON KS 1587” CAP FOR THIS CORNER. WATSON APPARENTLY HAS NOT SENT A REVISED LAND SURVEY REFERENCE WITH THE CORRECTED INFORMATION AS OF DECEMBER 28, 2017.

NOTE: HE DEEMED THE CORNER OBLITERATED BUT HE “SET” THIS CORNER BY SINGLE PROPORTION MEASUREMENT AS A LOST CORNER. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.

- 15) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MAY 29, 2020, FOR THE DATE OF SURVEY MAY 1, 2020, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT THE ORIGINAL STONE AT THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS **OBLITERATED** DUE TO THE ROAD CUT.

HE SET THIS CORNER BY SINGLE PROPORTION MEASUREMENT BETWEEN A FOUND 5/8” REBAR FILED WITH AN ORANGE LYON COUNTY CAP HALF-WAY TO THE NORTH AND A MAG NAIL WITH WASHER PROPERLY ESTABLISHED HALF-WAY TO THE SOUTH.

HE SET A 1/2” REBAR WITH HIS BLUE “WATSON KS 1587” CAP FOR THE WEST QUARTER CORNER OF SECTION 31, TOWNSHIP 17, RANGE 13.

HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 35.1’ NORTH 53°08’ EAST TO THE FOUND FACE OF A 6” STEEL BRACE POST
- 2) 31.2’ NORTH 65°02’ EAST TO THE FOUND FACE OF A 6” STEEL CORNER POST
- 3) 19.9’ SOUTH 89°53’ WEST TO A SET 3/8” REBAR

HIS HORIZONTAL TIES ARE CONTINUED PAGE 8

- 4) 22.2' SOUTH 88°31' WEST TO A FOUND T-POST IN A NORTH AND SOUTH FENCE LINE

NOTE: MR WATSON FAILED TO MENTION IN THIS REPORT THAT HIS CREW HAD EXCAVATED FOR THE STONE AT THIS CORNER IN OCTOBER 2017 AS NOTED BY LYON COUNTY ENGINEERING TECHNICIAN MATT COLLINS. THIS APPEARS TO BE A DUPLICATE OF HIS OCTOBER 13, 2017, REFERENCE REPORT WHEN HE ORIGINALLY SET THE 1/2" REBAR WITH HIS BLUE "WATSON KS 1587" CAP FOR THIS CORNER. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.

- 16) JOHN F. WATSON, P.S. 1587, OF SURVEYING AND MAPPING, L.L.C. FROM MIDLAND, TEXAS, IN A LAND SURVEY DATED NOVEMBER 29, 2021, FOR HIS PROJECT NUMBER 1021060678, WITH A DATE OF SURVEY OCTOBER 29, 2021, SAID THAT **HE FOUND THE EXISTING 1/2" REBAR WITH HIS BLUE CAP "WATSON KS 1587"** AT THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 PER LAND SURVEY REFERENCE REPORTS 213043 AND 222031 (AT THE *KANSAS STATE HISTORICAL SOCIETY*).

HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 35.1' NORTH 53°08' EAST TO THE FOUND FACE OF A 6" STEEL BRACE POST
- 2) 31.2' NORTH 65°02' EAST TO THE FOUND FACE OF A 6" STEEL CORNER POST
- 3) 19.9' SOUTH 89°53' WEST TO A SET 3/8" REBAR
- 4) 20.5' SOUTH 76°43' WEST TO A FOUND T-POST IN A NORTH AND SOUTH FENCE LINE

WEST QUARTER CORNER 32-17-13