

WEST 1/4 CORNER OF SECTION 33, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 623 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 3"** FOR THE QUARTER CORNER BETWEEN SECTIONS 32 AND 33, TOWNSHIP 17, RANGE 13 ON OCTOBER 13, 1860.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 18" X 13" X 4" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 AND 33, TOWNSHIP 17, RANGE 13.
2) 40.00 CHAINS SOUTH TO THE 24" X 12" X 3" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 32 AND 33, TOWNSHIP 17, RANGE 13 ON THE SOUTH TOWNSHIP BOUNDARY.

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 28 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 83 TO ESTABLISH THE PERMANENT CENTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13, AND TO SUBDIVIDE THE NORTHEAST 1/4 INTO THE EAST 1/2, AND TO ESTABLISH THE NORTHWEST AND THE SOUTHWEST 1/4'S, THAT HE SURVEYED ON JUNE 25, 1874.

HE SAID THAT **HE FOUND** THE QUARTER SECTION CORNER BETWEEN SECTIONS 33 AND 33, TOWNSHIP 17, RANGE 13 ON THIS **PERMANENT SURVEY**.

HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER IN HIS FIELD NOTES ON THIS **PERMANENT SURVEY**, BUT THE MONUMENT OF RECORD FOR THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 WAS THE **GLO LIMESTONE 15" X 12" X 3"**.

HE USED THIS CORNER AND THE EAST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 TO SET A 20" X 10" X 4" STONE FOR THE PERMANENT CENTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 ON THIS **PERMANENT SURVEY**.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 41 OF THE 8TH TERM RECORDED IN SURVEY BOOK "C" ON PAGE 98, A ROAD SURVEY FOR A COUNTY ROAD IN TOWNSHIP 17, RANGE 13 PETITIONED FOR BY HUGH R. HOLMES, ET. AL. THAT HE SURVEYED ON SEPTEMBER 16, 1874.

HE SHOWS ON HIS *PLAT OF SURVEY* IN PACKET 266 THAT THIS ROAD PASSES OVER THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13, BUT HE DOES NOT CALL OUT THIS CORNER IN HIS FIELD NOTES.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 WAS THE **GLO LIMESTONE 15" X 12" X 3"**.

THE *PLAT OF SURVEY* FOR THIS ROAD SURVEY IS RECORDED IN PACKET 266 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE.

HIS FIELD NOTES AND *PLAT OF SURVEY* IN PACKET 266 SHOWS THE FOLLOWING:

- 1) BEGAN AT THE NORTHEAST CORNER OF SECTION 29, TOWNSHIP 17, RANGE 13, THENCE SOUTH ON THE SECTION LINE 2,640 FEET TO THE QUARTER SECTION CORNER; THENCE SOUTH ON SAID LINE 269 FEET AND SET ANGLE STONE ABOUT 50 FEET NORTH OF THE CENTER OF DUCK CREEK, THENCE SOUTH 4°53' WEST 350 FEET TO THE TOP OF THE BANK ALONG SLOPE, 410 FEET BOTTOM OF BANK, 445 FEET SET ANGLE STONE, THENCE SOUTH 34°25' EAST 495 SET ANGLE STONE, THENCE SOUTH 88° EAST 520 FEET THE MIDDLE OF CREEK COURSES NORTH, 635 FEET SET ANGLE STONE ON SECTION LINE, THENCE SOUTH ON SAID LINE 2,076 FEET SET ANGLE STONE ON SECTION LINE, THENCE SOUTH 26°10' WEST 2,275 FEET AND SET ANGLE STONE, THENCE SOUTH 50° EAST 2,527 FEET AND SET ANGLE STONE, THENCE SOUTH 63°25' EAST 2,640 FEET SET MILE

STONE MARKED "1/M"; THENCE 230 FEET SMALL CREEK COURSES NORTHEAST, 297 FEET SET ANGLE STONE, THENCE SOUTH 67° WEST 509 FEET SET ANGLE STONE 38 FEET NORTH OF CORNER TO SECTIONS 28, 29, 32 AND 33, THENCE SOUTH 28°15' WEST 920 FEET SET ANGLE STONE, THENCE SOUTH 17° EAST 1,251 FEET RAVINE COURSES WEST OF NORTH, 1,400 FEET LEAVE RAVINE, 2,540 FEET SET ANGLE STONE ON SECTION LINE, THENCE SOUTH ON THE SECTION LINE TO THE CORNER TO SECTION 32 AND 33 [ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY].

- 2) TOTAL DISTANCE 2 MILES 38-3/4 RODS.
- 3) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 215 [PACKET 266 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY H. F. HOLMES AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17, RANGE 13 THAT HE SURVEYED ON SEPTEMBER 16, 1874.

HE SAID THAT **HE FOUND** THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 WAS THE **GLO LIMESTONE 15" X 12" X 3"**.

THERE WERE NO FIELD NOTES OR *PLAT OF SURVEY* FOR THIS ROAD SURVEY RECORDED ON PAGE 215.

NOTE: SEE PACKET 266 FOR THE FIELD NOTES AND *PLAT OF SURVEY* FOR THIS ROAD SURVEY.

HIS FIELD NOTES AND *PLAT OF SURVEY* IN PACKET 266 SHOW THE FOLLOWING:

- 1) BEGINNING AT THE *NE1/4* [PETITION STATES "NORTHEAST CORNER"] OF SECTION 29, TOWNSHIP 17, RANGE 13 AND RUNNING SOUTH ON THE SECTION LINE 176.3 RODS; THENCE SOUTH 44°53' WEST 10.66 RODS; THENCE SOUTH 34°25' EAST 3 RODS; THENCE SOUTH 88° EAST 11.5 RODS CROSSING DUCK CREEK AND INTERSECTING THE SECTION LINE; THENCE SOUTH ON THE SECTION LINE 87.33 RODS; THENCE SOUTH 26°20' WEST 12.12 RODS; THENCE SOUTH 7°50' EAST 15.27 RODS; THENCE SOUTH 63°25' EAST 24.84 RODS; THENCE SOUTH 67° WEST 12.84 RODS; THENCE SOUTH 28°15' WEST 24.9 RODS; THENCE SOUTH 17° EAST 98.18 RODS TO INTERSECT THE SECTION LINE; THENCE SOUTH ON THE SECTION LINE 44.84 RODS TO THE QUARTER SECTION CORNER BETWEEN SECTIONS 32 AND 33; THENCE SOUTH TO THE SECTION CORNER BETWEEN SECTIONS 32 AND 33, 4 AND 5 ON TOWNSHIPS 17 AND 18 RANGE 13 [AT THE TERMINUS OF THIS ROAD SURVEY].
- 2) TOTAL DISTANCE 2 MILES 38-3/4 RODS.
- 3) VIEWERS RECOMMENDED THAT THE ROAD BE GRANTED ACCORDING TO THE SURVEY AND *PLAT*, AND THAT SAID ROAD BE 50 FEET WIDE AS LOCATED AND SURVEYED.
- 4) THE ROAD WAS ESTABLISHED ON OCTOBER 5, 1874, AND WAS ATTESTED BY J. S. CRAIG, COUNTY CLERK.

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR A COUNTY ROAD IN TOWNSHIP 17, RANGE 13 RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE OF PAGE 158 THAT HE SURVEYED ON MAY 13, 1878.

HE SAID THAT **HE FOUND** THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 TO COMMENCE THIS ROAD SURVEY.

HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER TO COMMENCE THIS ROAD SURVEY IN HIS FIELD NOTES, BUT THE MONUMENT OF RECORD FOR THE EAST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS THE **GLO LIMESTONE 15" X 12" X 3"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13, I RAN WEST VARIATION 10°45' [ON THE QUARTER SECTION LINE FOR] 5,280 FEET TO THE QUARTER CORNER ON THE WEST LINE OF SECTION 32, TOWNSHIP 17, RANGE 13; THENCE WEST ON THE QUARTER SECTION LINE 5,280 FEET TO THE 1/4 CORNER ON THE WEST LINE OF SECTION 31, TOWNSHIP 17, RANGE 13 [ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY].
 - 2) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE OF PAGE 236 FOR A COUNTY ROAD SURVEY IN TOWNSHIP 17, RANGE 13 THAT HE SURVEYED ON JANUARY 2, 1882.

HE SAID THAT **HE FOUND** THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 TO BEGIN THE ROAD **VACATED** ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER TO BEGIN THIS ROAD SURVEY IN HIS FIELD NOTES, BUT THE MONUMENT OF RECORD FOR THE EAST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS THE **GLO LIMESTONE 15" X 12" X 3"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13; THENCE SOUTH 10°45' EAST 2,640 FEET TO THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 [AT THE TERMINUS OF THIS ROAD SURVEY].
 - 2) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.
 - 3) HE NOTED ON HIS *PLAT OF SURVEY* THAT THE ROAD FROM THE WEST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 EXTENDING EAST ONE MILE TO THE EAST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS TO BE **VACATED** BUT HE DID NOT SO STATE IN HIS FIELD NOTES.
- 7) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 152 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 194 TO 196 PETITIONED BY WILLIAM GERAGHTY AND OTHERS FOR THE LOCATION AND **VACATION** OF A COUNTY ROAD IN SECTION 32, TOWNSHIP 17, RANGE 13 [PACKET 440 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JANUARY 2, 1882.

HE SAID THAT **HE FOUND** THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 TO BEGIN THE ROAD **VACATED** ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER TO BEGIN THIS ROAD SURVEY IN HIS FIELD NOTES, BUT THE MONUMENT OF RECORD FOR THE EAST QUARTER CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS THE **GLO LIMESTONE 15" X 12" X 3"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13; THENCE SOUTH 10°45' EAST 2,640 FEET TO THE SOUTHWEST CORNER OF THE SOUTHWEST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 [ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY].
- 2) **THE ROAD PETITIONED TO BE VACATED:** COMMENCING AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13, THENCE WEST TO THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SAID SECTION 32, TOWNSHIP 17, RANGE 13.

- 3) THE VIEWERS REPORTED IN FAVOR OF LOCATING THE ROAD AS BEING NECESSARY FOR PUBLIC USE,
 - 4) THE VIEWERS FURTHER RECOMMENDED **VACATING** ALL THAT PORTION OF THE ROAD AS PRAYED FOR IN THE PETITION **EXCEPT 3 RODS OFF THE WEST END OF SAID ROAD**
 - 5) THE VIEWERS FURTHER DETERMINED THAT IF SAID ROAD BE LOCATED THAT ITS WIDTH SHALL BE **FIFTY (50) FEET.**
 - 6) THE ROAD WAS ESTABLISHED ON THE 5TH DAY OF JANUARY 1882 AS ROAD NUMBER 152 AND THAT THE TRUSTEES OF READING TOWNSHIP BE NOTIFIED TO CAUSE THE SAME TO BE OPENED FOR PUBLIC TRAVEL.
 - 7) THE FINAL ORDER WAS SIGNED BY J. M. GRIFFITH, CHAIRMAN.
 - 8) ROAD NUMBER 152 WAS RECORDED ON THE 12TH DAY OF JANUARY 1882 AND WAS ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK.
- 8) TIES FROM A SHEET FROM “MILES ENGINEERING AND SURVEYING” [GREGORY ALAN MILES, L.S. 667] IN THE SURVEY DRAWER WITH NO DATE, SHOWS A **1” BAR** AT THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13.
- NOTE: THERE IS NO INDICATION ON THE ORIGIN OF THIS 1” IRON BAR OR THE METHODOLOGY THAT HE USED TO DETERMINE THAT THIS 1” IRON BAR WAS THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13!! WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR.**
- 1) 54.55’ NORTH-NORTHEAST TO A NAIL AND BOTTLE CAP IN THE SIDE OF A CORNER FENCE POST
 - 2) 61.32’ EAST-SOUTHEAST TO A NAIL AND BOTTLE CAP IN THE TOP OF A CORNER FENCE POST
 - 3) 66.40’ SOUTH-SOUTHEAST TO A NAIL AND BOTTLE CAP IN THE TOP OF A CORNER FENCE POST
 - 4) IN LINE WITH A FENCE TO THE WEST
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SURVEY DATED FEBRUARY 17, 1998, FOR HIS PROJECT NUMBER 98030-02 AND FILED AS SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 17, RANGE 13, SAID THAT **HE FOUND AN EXISTING 5/8” REBAR OVER A 1” IRON PIN** AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 32, TOWNSHIP 17, RANGE 13 FROM THE EARLY 1980’S.
- HIS REFERENCE TIES ARE MISSING FROM THE SURVEY REFERENCE TIES FILE.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,224.61’ SOUTH TO THE 1/2” REBAR WITH HIS “LS 752” CAP THAT HE SET FOR THE NORTHEAST CORNER OF THE 10.00 ACRE TRACT, AS WITNESSED BY THE 1/2” REBAR WITH HIS “LS 752” CAP THAT HE SET AT 30 FEET WEST OF THE TRUE CORNER.
 - 2) 2,678.61’ SOUTH TO THE 1/2” REBAR WITH HIS “LS 752” CAP THAT HE SET FOR THE SOUTHEAST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 ON THE TOWNSHIP LINE.
- 10) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2017, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT **HE FOUND THE EXISTING RECORD 5/8” REBAR** AT THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 PER SURVEY REFERENCE REPORT 113021 AND PER CORNER TIE NOTES FILED BY STEVE BROSEMER, L.S 752, FROM THE LYON COUNTY ENGINEER’S OFFICE.
- HE SENT THE FOLLOWING HORIZONTAL TIES:**
- 1) **THIS RECOVERY REPORT HAS BEEN GENERATED PER KANSAS STATE REQUIREMENTS. SURVEY PREPARED HEREWITH IS ONGOING AND PART**

OF A LARGE PROJECT AND THUS THIS MONUMENTS POSITION HAS NOT YET BEEN FINALIZED AS THE TRUE CORNER LOCATION. SUBSEQUENT RECORD WILL BE FILED UPON COMPLETION OF THE ENTIRE SURVEY.

- 2) 35.7' NORTH 53°28' WEST TO A FOUND 40 D NAIL WITH WASHER IN A POWER POLE
 - 3) 61.4' SOUTH 70°44' EAST TO A FOUND CONCRETE NAIL IN A BOTTLE TOP IN THE TOP OF A WOOD FENCE POST
 - 4) 66.5' SOUTH 23°36' EAST TO A FOUND CONCRETE NAIL IN A BOTTLE TOP IN THE TOP OF A WOOD POST
 - 5) 55.6' NORTH 29°39' WEST TO A FOUND BENT 3" WOOD POST IN A FENCE
- 11) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 13, 2017, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT HE EXCAVATED THE COUNTY ROAD FOR THE ORIGINAL GLO STONE WITH A LYON COUNTY GRADER AT THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13, BUT HE DID **NOT** FIND THE STONE.
- HE FOUND THE EXISTING RECORD 5/8" REBAR** AT THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 PER SURVEY REFERENCE REPORT 113021 AND PER CORNER TIE NOTES FILED BY STEVE BROSEMER, L.S. 752 FROM THE LYON COUNTY ENGINEER'S OFFICE.
- HE SENT THE FOLLOWING HORIZONTAL TIES:**
- 1) 35.7' NORTH 53°28' WEST TO A FOUND 40 D NAIL WITH WASHER IN A POWER POLE
 - 2) 61.4' SOUTH 70°44' EAST TO A FOUND CONCRETE NAIL IN A BOTTLE TOP IN THE TOP OF A WOOD FENCE POST
 - 3) 66.5' SOUTH 23°36' EAST TO A FOUND CONCRETE NAIL IN A BOTTLE TOP IN THE TOP OF A WOOD POST
 - 4) 55.6' NORTH 29°39' WEST TO A FOUND BENT 3" WOOD POST IN A FENCE
- 12) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MAY 29, 2020, FOR THE DATE OF SURVEY MAY 1, 2020, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT HE EXCAVATED THE COUNTY ROAD FOR THE ORIGINAL STONE AT THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 WITH A LYON COUNTY GRADER, BUT NOTHING WAS FOUND.
- HE FOUND THE EXISTING RECORD 5/8" REBAR** AT THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13 PER SURVEY REFERENCE REPORT 113021 AND PER CORNER TIE NOTES FILED BY STEVE BROSEMER, L.S. 752, FROM THE LYON COUNTY ENGINEER'S OFFICE.
- HE SENT THE FOLLOWING HORIZONTAL TIES:**
- 1) 61.4' SOUTH 70°44' EAST TO A FOUND CONCRETE NAIL AND BOTTLECAP IN THE TOP OF A WOOD POST
 - 2) 66.5' SOUTH 23°36' EAST TO A FOUND CONCRETE NAIL AND BOTTLECAP IN THE TOP OF A WOOD POST
 - 3) 55.6' NORTH 29°39' WEST TO A FOUND BENT 3" WOOD POST IN A FENCE
- NOTE:** THIS APPEARS TO BE A DUPLICATE OF HIS OCTOBER 2017 LAND SURVEY REFERENCE REPORT. LYON COUNTY DID **NOT** EXCAVATE FOR THIS CORNER AGAIN IN MAY 2020. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.
- 13) JOHN F. WATSON, P.S. 1587, OF SURVEYING AND MAPPING, L.L.C. FROM MIDLAND, TEXAS, IN A LAND SURVEY DATED NOVEMBER 29, 2021, FOR HIS PROJECT NUMBER 1021060678, WITH A DATE OF SURVEY OCTOBER 29, 2021, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR** AT THE WEST QUARTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13.

HE NOTED: PREVIOUSLY EXCAVATED THE COUNTY ROAD FOR THE ORIGINAL STONE WITH A LYON COUNTY GRADER; NOTHING FOUND. THE FOUND 5/8" REBAR PER SURVEY REFERENCE REPOT 113021 (AT THE *KANSAS STATE HISTORICAL SOCIETY*) AND PER CORNER TIE NOTES FILED BY DEPUTY COUNTY SURVEYOR STEVE BROSEMER, L.S. 752, FROM THE LYON COUNTY ENGINEER'S OFFICE.

FOUND PER LAND SURVEY REFERENCE REPORTS 113021, 213044, AND 222033 (AT THE *KANSAS STATE HISTORICAL SOCIETY*).

HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 35.7' NORTH 53°28' WEST TO A FOUND 40 D NAIL WITH WASHER IN A POWER POLE
- 2) 41.0' NORTH 45°20' WEST TO A FOUND 5" PIPE POST FENCE CORNER
- 3) 61.4' SOUTH 70°44' EAST TO A FOUND CONCRETE NAIL IN BOTTLECAP IN THE TOP OF A WOOD POST
- 4) 66.5' SOUTH 23°36' EAST TO A FOUND CONCRETE NAIL IN BOTTLECAP IN THE TOP OF A WOOD POST

WEST QUARTER CORNER 33-17-13