

NORTHWEST CORNER SECTION 34, TOWNSHIP 17 SOUTH, RANGE 13 EAST

1) ON PAGE 618 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 11" X 3"** FOR THE CORNER TO SECTIONS 27, 28, 33 AND 34, TOWNSHIP 17, RANGE 13 ON OCTOBER 12, 1860, FROM WHICH:

- 1) A BLACK WALNUT TREE 12" IN DIAMETER BEARS SOUTH 4°30' EAST AT 70 LINKS DISTANCE.
- 2) A BLACK WALNUT TREE 12" IN DIAMETER BEARS NORTH 65°30' EAST AT 40 LINKS DISTANCE.
- 3) AN ELM TREE 18" IN DIAMETER BEARS SOUTH 70° WEST AT 70 LINKS DISTANCE
- 4) AN ELM TREE 12" IN DIAMETER BEARS NORTH 30° WEST AT 75 LINKS DISTANCE.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH TO THE 18" X 12" X 3" LIMESTONE THAT THEY SET FOR THE QUARTER CORNER BETWEEN SECTIONS 33 AND 34, TOWNSHIP 17, RANGE 13.
- 2) 80.00 CHAINS SOUTH TO THE 20" X 12" X 3" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 33 AND 34, TOWNSHIP 17, RANGE 13 ON THE SOUTH TOWNSHIP BOUNDARY.
- 3) 40.00 CHAINS EAST TO THE 14" X 12" X 3" LIMESTONE THAT THEY SET FOR THE QUARTER CORNER BETWEEN SECTIONS 27 AND 34, TOWNSHIP 17, RANGE 13.
- 4) 80.00 CHAINS EAST TO THE BLACK WALNUT TREE, 5" IN DIAMETER, MARKED FOR THE CORNER TO SECTIONS 27 AND 34, TOWNSHIP 17, RANGE 13 ON THE EAST COUNTY LINE.

2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 201 TO 202 [PACKET 57 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY T. J. PRICE AND OTHERS FOR TWO COUNTY ROADS IN TOWNSHIPS 16, 17 AND 18 IN RANGE 13 THAT HE SURVEYED ON APRIL 15, 16 AND 17, 1872.

HE SHOWS ON HIS *PLAT OF SURVEY* THAT THE FIRST ROAD PASSES THROUGH THE NORTHWEST CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 ON THIS ROAD SURVEY, BUT HE DID NOT CALL OUT THIS CORNER IN HIS FIELD NOTES.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER IN HIS FIELD NOTES ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE NORTHWEST CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 WAS THE **GLO LIMESTONE 16" X 11" X 3"**.

HIS FIELD NOTES FOR THE FIRST ROAD ARE AS FOLLOWS:

- 1) BEGINNING AT A STONE NEAR THE RIGHT BANK OF ELM CREEK AT THE CROSSING OF THE STATE ROAD IN SECTION 32, TOWNSHIP 1, RANGE 13 AND RUNNING SOUTH 63° EAST 8-6/10 RODS TO THE LINE BETWEEN SECTIONS 32 AND 33 AT 83.5 RODS NORTH OF THE SECTION CORNER; THENCE SOUTH ON THE SECTION LINE TO THE QUARTER CORNER BETWEEN SECTIONS 16 AND 17, TOWNSHIP 17, RANGE 13; THENCE SOUTH ON SAID LINE 7 RODS; THENCE SOUTH 61°10' EAST 24-1/4 RODS; THENCE SOUTH 19°21' EAST 8-8/10 RODS CROSSING 142 MILE CREEK; THENCE SOUTH 71°50' WEST 23-2/3 RODS TO THE LINE BETWEEN SECTIONS 16 AND 17; THENCE SOUTH ON SAID LINE 179 RODS; THENCE SOUTH 17°50' WEST 12-1/2 RODS; THENCE SOUTH 49°35' EAST 23-4/10 RODS TO THE LINE BETWEEN SECTION 20 AND 21; THENCE SOUTH ON SAID LINE TO THE CORNER TO SECTIONS 20, 21, 28 AND 29; THENCE EAST BETWEEN SECTIONS 21 AND 28 253-1/3 RODS; THENCE SOUTH 63°35' EAST 47 RODS; THENCE NORTH 78°15' EAST 28 RODS TO THE LINE BETWEEN SECTIONS 27 AND 28; THENCE SOUTH ON SAID LINE 210-1/3 RODS; THENCE SOUTH 7° WEST 12 RODS; THENCE SOUTH 30° EAST 14-1/4 RODS TO THE LINE BETWEEN SECTIONS

27 AND 28; THENCE SOUTH ON SAID LINE 14-2/3 RODS CROSSING DUCK CREEK; THENCE SOUTH 5° WEST 45-4/10 RODS; THENCE SOUTH 20° EAST 19-1/2 RODS; THENCE SOUTH 47°20' EAST 8 RODS; THENCE SOUTH 74°30' EAST 18 RODS TO THE LINE BETWEEN SECTIONS 33 AND 34; THENCE SOUTH ON SAID LINE TO THE CORNER TO SECTION 3, 4, 33 AND 34 TOWNSHIPS 17 AND 18, RANGE 13; THENCE EAST ON THE TOWNSHIP LINE BETWEEN SECTIONS 3 AND 34 TO THE EAST LINE OF LYON COUNTY.

- 2) TOTAL DISTANCE FOR THE FIRST ROAD 8 MILES AND 93 RODS.
 - 3) THE VIEWERS RECOMMENDED THAT THE ROAD SHOULD BE OPENED AND ESTABLISHED, AND TO BE FIFTY (50) FEET WIDE, AS LOCATED AND SURVEYED.
 - 4) THE ROAD WAS ORDERED ESTABLISHED AT A MEETING OF THE COUNTY BOARD HELD MAY 20, 1872, AS A 50-FOOT-WIDE ROAD.
 - 5) THE FINAL ORDER WAS ATTESTED TO BY DAVID S. GILMORE, COUNTY CLERK.
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 28 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 83 TO ESTABLISH THE PERMANENT CENTER CORNER OF SECTION 33, TOWNSHIP 17, RANGE 13, AND TO SUBDIVIDE THE NORTHEAST 1/4 INTO THE EAST 1/2 AND TO ESTABLISH THE NORTHWEST AND THE SOUTHWEST 1/4'S, THAT HE SURVEYED ON JUNE 25, 2021.

HE SAID THAT **HE FOUND** THE CORNER TO SECTIONS 27, 27, 33 AND 34, TOWNSHIP 17, RANGE 13 ON THIS **PERMANENT SURVEY**.

HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER IN HIS FIELD NOTES ON THIS **PERMANENT SURVEY**, BUT THE MONUMENT OF RECORD FOR THE NORTHWEST CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 WAS THE **GLO LIMESTONE 16" X 11" X 3"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) 1,336-1/2' WEST VARIATION 10°30' EAST TO THE 20" X 16" X 4" STONE THAT HE SET FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE NORTHEAST 1/4 OF SECTION 33, TOWNSHIP 17, RANGE 13.
- 2) 2,673' WEST VARIATION 10°30' EAST TO THE QUARTER SECTION CORNER BETWEEN SECTIONS 28 AND 33, TOWNSHIP 17, RANGE 13.

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER ONE HUNDRED FORTY-EIGHT, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 148 THAT WAS ORDERED BY THE PATTON BROTHERS TO PERMANENTLY ESTABLISH THE CORNER TO SECTIONS 15, 16, 21 AND 22 IN TOWNSHIP 17, RANGE 13, THAT HE SURVEYED ON SEPTEMBER 24 AND 25, 1886.

HE APPARENTLY **FOUND** THE SOUTHEAST CORNER OF SECTION 28, TOWNSHIP 17, RANGE 13 ON THIS **PERMANENT SURVEY**.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND IN HIS FILED NOTES ON THIS **PERMANENT SURVEY**, BUT THE MONUMENT OF RECORD FOR THE SOUTHEAST CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 WAS THE **GLO LIMESTONE 16" X 11" X 3"**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) 5,272' NORTH TO THE "BASE OF THE SECTION CORNER POST" THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 27, TOWNSHIP 17, RANGE 13.
- 2) 7,911.5' NORTH TO THE 4" X 10" X 15" LIMESTONE MARKED "1/4" THAT HE SET **2 FEET TOO FAR EAST** OF THE TRUE POSITION FOR THE WEST QUARTER CORNER OF SECTION 22, TOWNSHIP 17, RANGE 13.
- 3) 10,551.5' NORTH TO THE TRUE POSITION FOR THE CORNER TO SECTIONS 15, 16, 21 AND 22, TOWNSHIP 17, RANGE 13 – NO STONE WAS SET ON THIS PERMANENT SURVEY DUE TO A ROCK LEDGE. AN ELM TREE 24" IN DIAMETER BEARS NORTH 83° WEST 56 FEET, AN ELM TREE 18" IN DIAMETER BEARS SOUTH 76°20'

WEST 54 FEET, AND A RED OAK TREE 15" IN DIAMETER BEARS SOUTH 66°30' EAST 85 FEET.

- 4) 13,191' NORTH TO THE STONE THAT HE FOUND AT THE WEST QUARTER CORNER OF SECTION 15, TOWNSHIP 17, RANGE 13.

- 5) THE CORPS OF ENGINEERS FOR THE MELVERN LAKE BOUNDARY SURVEY IN DECEMBER 1974, LARGE SURVEY SR #27001 IN THE LARGE SURVEY DRAWER FOR TOWNSHIP 17, RANGE 13, SAID THAT THEY DID **NOT** SET THE SOUTHWEST CORNER OF SECTION 27, TOWNSHIP 17, RANGE 13 AS IT FALLS IN DUCK CREEK.

THEY DID SET THE FOLLOWING **WITNESS CORNERS**:

- A) **CORPS OF ENGINEERS STANDARD CONCRETE MONUMENT 66.73 FEET NORTH OF THE TRUE CORNER:** 42 FEET NORTH OF THE RIGHT HIGH BANK OF DUCK CREEK, AND 100 FEET EAST OF THE CENTERLINE OF A COUNTY GRAVEL ROAD, AND AT THE EDGE OF BRUSH, WITH A CORPS OF ENGINEERS STANDARD WITNESS POST.

- 1) 16.20' WEST-SOUTHWEST TO A NAIL AND BOTTLECAP IN A 16" HACKBERRY TREE
- 2) 30.33' SOUTH-SOUTHWEST TO A NAIL AND BOTTLECAP IN A 10" BOX ELDER TREE
- 3) 32.70' SOUTH-SOUTHEAST TO A NAIL AND BOTTLECAP IN A 12" BOX ELDER TREE
- 4) 16.49' EAST TO A NAIL AND BOTTLECAP IN A 6" MULBERRY TREE

- B) **CORPS OF ENGINEERS STANDARD CONCRETE MONUMENT 37.6 FEET SOUTH OF THE TRUE CORNER:** 24 FEET SOUTH OF THE WATER'S EDGE ON THE SOUTH SIDE OF DUCK CREEK, IN WOODS, WITH CORPS OF ENGINEERS STANDARD WITNESS POST

- 1) 20.16' WEST TO A NAIL AND BOTTLE CAP IN A 4" COTTONWOOD TREE
- 2) 7.68' SOUTHEAST TO A NAIL AND BOTTLE CAP IN A 18" HACKBERRY TREE
- 3) 30.33' SOUTH-SOUTHEAST TO A NAIL AND BOTTLE CAP IN A 16" MULBERRY TREE
- 4) 16.16' NORTHEAST TO A NAIL AND BOTTLE CAP IN A 4" MULBERRY TREE

THEIR DRAWING SHOWS THE FOLLOWING FROM THE TRUE POSITION:

- 1) 66.73' NORTH ON THE SECTION LINE TO THE STANDARD CORPS OF ENGINEERS MONUMENT THAT THEY SET.
- 2) 1,435.95' NORTH TO THE **PROPERTY STONE** THAT THEY FOUND.
- 3) 2,641.05' NORTH TO THE STONE THAT THEY FOUND AT THE WEST QUARTER CORNER OF SECTION 27, TOWNSHIP 17, RANGE 13.
- 4) 5,302.80' NORTH TO THE 3/4" REBAR THAT THEY SET FOR THE NORTHWEST CORNER OF SECTION 27, TOWNSHIP 17, RANGE 13.
- 5) 1,323.80' EAST TO THE CORPS OF ENGINEERS MONUMENT THAT THEY SET FOR THE SOUTH 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 27, TOWNSHIP 17, RANGE 13.
- 6) 2,647.59' EAST TO THE THEORETICAL LOCATION FOR THE SOUTH QUARTER CORNER OF SECTION 27, TOWNSHIP 17, RANGE 13 – NO MONUMENT SET.
- 7) 5,295.18' EAST TO THE CHISELED CROSS THAT THEY SET IN THE CONCRETE BRIDGE DECK OVER THE MARIAS DES CYGNES RIVER AT THE SOUTHEAST CORNER OF SECTION 27, TOWNSHIP 17, RANGE 13 ON THE LYON AND OSAGE COUNTY LINE.

- 6) THE CORPS OF ENGINEERS FOR THE MELVERN LAKE BOUNDARY SURVEY IN DECEMBER 1974, LARGE SURVEY SR #34001 IN THE LARGE SURVEY DRAWER FOR TOWNSHIP 17, RANGE 13, SAID THAT THEY DID **NOT** SET THE NORTHWEST CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 AS IT FALLS IN DUCK CREEK. THEY DID SET THE FOLLOWING **WITNESS CORNERS**:

THEIR INFORMATION IS CONTINUED PAGE 4

A) **CORPS OF ENGINEERS STANDARD CONCRETE MONUMENT 66.73 FEET NORTH OF THE TRUE CORNER:** 42 FEET NORTH OF THE RIGHT HIGH BANK OF DUCK CREEK, AND 100 FEET EAST OF THE CENTERLINE OF A COUNTY GRAVEL ROAD, AND AT THE EDGE OF BRUSH, WITH A CORPS OF ENGINEERS STANDARD WITNESS POST.

- 1) 16.20' WEST-SOUTHWEST TO A NAIL AND BOTTLECAP IN A 16" HACKBERRY TREE
- 2) 30.33' SOUTH-SOUTHWEST TO A NAIL AND BOTTLECAP IN A 10" BOX ELDER TREE
- 3) 32.70' SOUTH-SOUTHEAST TO A NAIL AND BOTTLECAP IN A 12" BOX ELDER TREE
- 4) 16.49' EAST TO A NAIL AND BOTTLECAP IN A 6" MULBERRY TREE

B) **CORPS OF ENGINEERS STANDARD CONCRETE MONUMENT 34.76 FEET SOUTH OF THE TRUE CORNER:** 24 FEET SOUTH OF THE WATER'S EDGE ON THE SOUTH SIDE OF DUCK CREEK, IN WOODS, WITH A CORPS OF ENGINEERS STANDARD WITNESS POST.

- 1) 20.16' WEST TO A NAIL AND BOTTLE CAP IN A 4" COTTONWOOD TREE
- 2) 27.68' SOUTHEAST TO A NAIL AND BOTTLE CAP IN A 18" HACKBERRY TREE
- 3) 30.33' SOUTH-SOUTHEAST TO A NAIL AND BOTTLE CAP IN A 16" MULBERRY TREE
- 4) 16.16' NE TO A NAIL AND BOTTLE CAP IN A 4" MULBERRY TREE

THEIR DRAWING SHOWS THE FOLLOWING FROM THE TRUE POSITION:

- 1) 1,323.80' EAST TO THE CORPS OF ENGINEERS MONUMENT THAT THEY SET FOR THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 34, TOWNSHIP 17, RANGE 13.
- 2) 2,647.59 TO THE THEORETICAL LOCATION FOR THE NORTH QUARTER CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 – NO MONUMENT SET.
- 3) 5,295.18' EAST TO THE CHISELED CROSS THAT THEY SET IN THE CONCRETE BRIDGE DECK OVER THE MARIAS DES CYGNES RIVER AT THE NORTHEAST CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 ON THE LYON AND OSAGE COUNTY LINE.
- 4) 34.76' SOUTH ON THE SECTION LINE TO THE STANDARD CORPS OF ENGINEERS MONUMENT THAT THEY SET.
- 5) 2,640.82' SOUTH TO THE 3/4" REBAR THAT THEY SET FOR THE WEST QUARTER CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13.
- 6) 5,282.03' SOUTH TO THE 3/4" REBAR THAT THEY SET FOR THE SOUTHWEST CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 ON THE TOWNSHIP LINE.

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F34003 IN THE SURVEY FILE FOR TOWNSHIP 17, RANGE 13 DATED NOVEMBER 10, 2010, FOR THE SURVEY OF A 35.74 ACRE TRACT IN THE NORTHWEST 1/4 OF SECTION 34, TOWNSHIP 17, RANGE 13 FOR EMPORIA STATE UNIVERSITY, SHOWS ON HIS SURVEY THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 34, TOWNSHIP 17, RANGE 13, BUT THIS **THEORETICAL POSITION WAS NOT MONUMENTED** ON THIS SURVEY AS THE CORNER POSITION FALLS IN DUCK CREEK.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323.80' EAST TO THE CORPS OF ENGINEERS MONUMENT THAT HE FOUND ON THE MELVERN RESERVOIR BOUNDARY AT THE NORTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 34, TOWNSHIP 17, RANGE 13.
- 2) 5,295.49' EAST TO THE PLUS (+) CUT IN A BRIDGE DECK THAT HE FOUND AT THE NORTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 34, TOWNSHIP 17, RANGE 13 ON THE LYON COUNTY AND OSAGE COUNTY LINE.
- 3) 610.50' [37 RODS] SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR THE NORTHWEST CORNER OF THE 35.74 ACRE SURVEYED TRACT.

HIS INFORMATION IS CONTINUED PAGE 5

- 4) 990.82' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR A TRACT CORNER, BEING THE NORTHWEST CORNER OF THE "CITY TRACT".
 - 3) 2,640.82' SOUTH TO THE 3/4" REBAR THAT HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 34, TOWNSHIP 17, RANGE 13.
- 7) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2017, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT HE DEEMED THAT THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS **OBLITERATED**.
- HE SET THIS CORNER BY A THEORETICAL POSITION PROVIDED BY STEVEN BROSEMER IN SURVEY PLATS ON FILE WITH THE LYON COUNTY ENGINEER'S OFFICE. HE [BROSEMER] CALCULATED AND USED THE POSITION ON SURVEY PLATS BUT DID NOT SET THE POSITION OF THE MONUMENT AND HE SAID THAT THE POSITION FELL IN DUCK CREEK IN 2010. I WAS ABLE TO SET THE CORNER POSITION AND REFERENCES AS THE POSITION NO LONGER FELL IN THE CREEK AREA.**
- HE SET A 1/2" REBAR WITH BLUE CAP "WATSON KS 1587" FOR THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13.**
- HE SENT THE FOLLOWING HORIZONTAL TIES:**
- 1) **THIS RECOVERY REPORT HAS BEEN GENERATED PER KANSAS STATE REQUIREMENTS. SURVEY PREPARED HEREWITH IS ONGOING AND PART OF A LARGE PROJECT AND THUS THIS MONUMENTS POSITION HAS NOT YET BEEN FINALIZED AS THE TRUE CORNER LOCATION. SUBSEQUENT RECORD WILL BE FILED UPON COMPLETION OF THE ENTIRE SURVEY.**
 - 2) 100.1' SOUTH 82°21' WEST TO A SET 1/2" REBAR
 - 3) 150.0' SOUTH 82°21' WEST TO A SET 1/2" REBAR
 - 4) 200.1' SOUTH 82°21' WEST TO A SET 1/2" REBAR
- 8) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 12, 2017, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT HE DEEMED THAT THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13 WAS **OBLITERATED**.
- HE SET THIS CORNER BY A THEORETICAL POSITION PROVIDED BY STEVEN BROSEMER IN SURVEY PLATS ON FILE WITH THE LYON COUNTY ENGINEER'S OFFICE. HE [BROSEMER] CALCULATED AND USED THE POSITION ON SURVEY PLATS BUT DID NOT SET THE POSITION OF THE MONUMENT AND HE SAID THAT THE POSITION FELL IN DUCK CREEK IN 2010. I WAS ABLE TO SET THE CORNER POSITION AND REFERENCES AS THE POSITION NO LONGER FELL IN THE CREEK AREA.**
- HE SET A 1/2" REBAR WITH BLUE CAP "WATSON KS 1587" FOR THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13.**
- HE SENT THE FOLLOWING HORIZONTAL TIES:**
- 1) 100.1' SOUTH 82°21' WEST TO A SET 1/2" REBAR
 - 2) 150.0' SOUTH 82°21' WEST TO A SET 1/2" REBAR
 - 3) 200.1' SOUTH 82°21' WEST TO A SET 1/2" REBAR
- NOTE: THIS APPEARS TO BE A DUPLICATE OF HIS MARCH 10, 2017 LAND SURVEY REFERENCE REPORT AS HE KEEPS REFERRING TO THIS "OBLITERATED" CORNER AGAIN AFTER HE HAD SET IT. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.**
- 9) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MAY 29, 2020, FOR THE DATE OF SURVEY MAY 1, 2020, FOR HIS PROJECT NUMBER 16-0040, THE SURVEY

FOR THE READING WIND FARM, SAID THAT HE DEEMED THAT THE NORTHWEST CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 WAS **OBLITERATED**.

HE RESET THIS CORNER BY A THEORETICAL POSITION PROVIDED BY STEVEN BROSEMER IN SURVEY PLATS ON FILED WITH THE LYON COUNTY ENGINEER'S OFFICE. HE CALCULATED AND USED THE POSITION ON THE SURVEY PLATS BUT DID NOT SET THE POSITION OF MONUMENT AND SAID THE POSITION FELL IN DUCK CREEK IN 2010. MR. WATSON WAS ABLE TO SET THE CORNER POSITION AND REFERENCES AS THE CORNER NO LONGER FELL IN THE CREEK AREA.

HE SET A 1/2" REBAR WITH BLUE CAP "WATSON KS 1587" FOR THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 17, RANGE 13.

HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 100.1' SOUTH 82°21' WEST TO A SET 1/2" REBAR
- 2) 150.0' SOUTH 82°21' WEST TO A SET 1/2" REBAR
- 3) 200.1' SOUTH 82°21' WEST TO A SET 1/2" REBAR

NOTE: THIS APPEARS TO BE A DUPLICATE OF HIS MARCH 10, 2017, LAND SURVEY REFERENCE REPORT AS HE KEEPS REFERRING TO THIS "**OBLITERATED**" CORNER AGAIN AFTER HE HAD SET IT. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR.

- 10) JOHN F. WATSON, P.S. 1587, OF SURVEYING AND MAPPING, L.L.C. FROM MIDLAND, TEXAS, IN A LAND SURVEY DATED NOVEMBER 29, 2021, FOR HIS PROJECT NUMBER 1021060678, WITH A DATE OF SURVEY OCTOBER 29, 2021, SAID THAT **HE FOUND THE EXISTING 1/2" REBAR WITH HIS BLUE CAP "WATSON KS 1587"** AT THE NORTHWEST CORNER OF SECTION 34, TOWNSHIP 17, RANGE 13 PER LAND SURVEY REFERENCE REPORTS 223095 AND 213041 (AT THE *KANSAS STATE HISTORICAL SOCIETY*).

HE NOTED: CORNER IN GOOD STANDING.

HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 100.1' SOUTH 82°21' WEST TO A 1/2" REBAR
- 2) 150.0' SOUTH 82°21' WEST TO A 1/2" REBAR
- 3) 200.1' SOUTH 82°21' WEST TO A 1/2" REBAR

NORTHWEST CORNER 34-17-13