

NORTH 1/4 CORNER SECTION 01, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 68 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 10" X 4"** FOR THE NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE NORTH TOWNSHIP BOUNDARY ON DECEMBER 11, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE NORTH TOWNSHIP BOUNDARY TO THE 21" X 14" X 3' LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 1 AND 2, TOWNSHIP 19, RANGE 12
 - 2) 40.00 CHAINS EAST ON THE NORTH TOWNSHIP BOUNDARY TO THE 22" X 15" X 4" SANDSTONE THAT THEY SET FOR THE CORNER TO TOWNSHIPS 18 AND 19 SOUTH, RANGES 12 AND 13 EAST AT THE NORTHEAST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12
- 2) H. S. SLEEPER, DEPUTY COUNTY SURVEYOR FOR G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 26 FOR THE *FOREST HILL TO WATERLOO ROAD* [PACKET 164 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT WAS SURVEYED MARCH 15 AND 16, 1859.

HE APPARENTLY **FOUND** THE NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE WAS THE GLO **LIMESTONE**.

HIS SURVEY NOTES AND *PLAT OF SURVEY* SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE NORTH QUARTER CORNER OF SECTION 12, TOWNSHIP 19, RANGE 12; THENCE NORTH THROUGH THE MIDDLE OF SECTION 1 [TOWNSHIP 19, RANGE 12 TO THE NORTH QUARTER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE BY HIS *PLAT OF SURVEY*]; THENCE NORTH 45° EAST 226 RODS 7 LINKS TO THE EAST QUARTER CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12; THENCE NORTH ON THE TOWNSHIP LINE OF RANGES 12 AND 13 TO THE NORTHEAST CORNER OF SECTION 13, TOWNSHIP 17, RANGE 12; THENCE NORTH 48 RODS, 20 LINKS; THENCE NORTH 25° EAST 30 RODS; THENCE NORTH 7° EAST 96 RODS TO THE SOUTH LINE OF *WATERLOO TOWNSITE*; THENCE NORTH TO *MICHEL'S HOTEL IN WATERLOO*.
 - 2) ESTABLISHED ON APRIL 4, 1959
 - 3) A NOTE IN **RED** IN THE LEFT MARGIN OF PAGE 26 STATES: **COMMISSIONER'S RECORD PAGE 59**
 - 4) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY, SO BY THE TERRITORIAL LAW IN EFFECT IN CHAPTER 77, SECTION 66, APPROVED FEBRUARY 4, 1859, THE WIDTH WOULD BE FOUR RODS (66 FEET) WIDE.
- 3) JAMES MEANS, COUNTY SURVEYOR FROM 1865 TO 1867, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 57 [PACKET 394 FOR THE *PLAT OF SURVEY* AND PACKET 436 FOR THE PETITION IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY P. B. PLUMB AND OTHERS FOR A ROAD FROM THE *LAWRENCE AND EMPORIA ROAD* EAST ON THE TOWNSHIP LINE TO INTERSECT THE ROAD FROM *FOREST HILL TO WATERLOO* THAT WAS SURVEYED ON JANUARY 25, 1866.

HE APPARENTLY **FOUND** THE NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.

HIS INFORMATION IS CONTINUED PAGE 2

HE DID NOT DESCRIBE ANY OF THE SECTION CORNERS THAT HE FOUND OR THAT HE PASSED OVER ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THE NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE WAS THE GLO **LIMESTONE**.

NOTE: HE HAD MISLABELED THE SECTION CORNERS ON HIS *PLAT OF SURVEY*. WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR HIS SURVEY NOTES AND *PLAT OF SURVEY* SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT A STONE WHERE THE *LAWRENCE AND EMPORIA ROAD* CROSSES THE NORTH LINE OF TOWNSHIP 19 [NEAR THE NORTHWEST CORNER OF SECTION 2, TOWNSHIP 19, RANGE 11 BY HIS *PLAT OF SURVEY*], THENCE EAST ALONG SAID TOWNSHIP LINE 6 MILES; THENCE SOUTHEAST 30° [FOR] 6 CHAINS AND 70 LINKS TO A STONE SET IN THE GROUND MARKED “A II”; THENCE CROSSING BADGER CREEK TO A STONE SET IN THE GROUND SOUTHEAST 82° [FOR] 8 CHAINS; THENCE NORTHEAST 61° [FOR] 10 CHAINS; THENCE ON SAID LINE TO THE ROAD LEADING FROM *FOREST HILL TO WATERLOO* [NORTHEAST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 BY HIS *PLAT OF SURVEY*]
 - 2) A NOTE IN **RED** IN THE LEFT MARGIN STATES: **COMMISSIONER’S RECORD PAGE 122** AND THE DATE FEBRUARY 12, 1866
 - 3) RECORDED FEBRUARY 16, 1866 BY J. WILLIAMS, COUNTY CLERK
 - 4) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER SEVEN, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK “E” ON PAGE 7 THAT HE SURVEYED ON FEBRUARY 25TH AND 29TH, 1884 BY THE ORDER OF A. E. STOUGHTON TO SUBDIVIDE SECTION 1, TOWNSHIP 19, RANGE 12.

HE SAID THAT **HE FOUND THE GOVERNMENT STONE** AT THE NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.

HE DID NOT DESCRIBE ANY OF THE STONES THAT HE FOUND OR THAT HE SET ON THIS PERMANENT SURVEY, BUT THE **GOVERNMENT STONE** OF RECORD FOR THE NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE WAS THE GLO **LIMESTONE**.

HE COMMENTED THAT “QUARTER CORNERS ALL IN, I COMMENCED BY ESTABLISHING THE CENTER CORNER BY INTERSECTION” ON THIS **PERMANENT SURVEY**.

HE NOTED ON HIS *PLAT OF SURVEY* THAT THIS CORNER IS THE NORTHEAST CORNER OF THE A. E. STOUGHTON TRACT AND THE NORTHWEST CORNER OF THE A. G. STEVENSON TRACT.

HIS FIELD NOTES AND *PLAT OF SURVEY* SHOWS THE FOLLOWING INFORMATION:

- 1) 20.00 CHAINS EAST VARIATION 9°56’ ON THE TOWNSHIP LINE TO THE STONE THAT HE FOUND AT THE 1/8TH CORNER ON THE NORTH SIDE OF THE NE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 12, BEING THE NORTHEAST CORNER OF THE A. G. STEVENSON TRACT AND THE NORTHWEST CORNER OF THE H. BATCH TRACT
 - 2) 40.00 CHAINS EAST VARIATION 9°56’ ON THE TOWNSHIP LINE TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 AT THE TOWNSHIP CORNER, BEING THE NORTHEAST CORNER OF THE H. BATCH TRACT
 - 3) 40.00 CHAINS WEST VARIATION 9°56’ ON THE TOWNSHIP LINE TO THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12, BEING THE NORTHWEST CORNER OF THE A. E. STOUGHTON TRACT
- 5) REA BOOK 30 ON PAGE 38 SAYS THAT **THEY SET AN IRON PIN** FOR THE SOUTH QUARTER CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12 ON THE TOWNSHIP LINE AT 2,639.8 FEET BETWEEN THE SOUTHWEST CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12 AND THE SOUTHEAST CORNER OF SECTION 36, TOWNSHIP

18, RANGE 12. THERE WAS NO DESCRIPTION OF THE **IRON PIN** THAT THEY SET FOR THIS CORNER OR THE WITNESS PIN THAT THEY SET ON THIS PAGE.

VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR

1) 21.66' NORTH TO A WITNESS PIN

- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18, RANGE 12 SHOWS A **1" SQUARE IRON PIN** AT THE SOUTH QUARTER CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12 ON THE TOWNSHIP LINE.

VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN MAY BE THE "REA PIN"!! WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR

1) 27.3' NORTH TO A SPIKE IN THE TOP OF THE EAST GATE POST BRACE

2) 36.9' SE TO A SPIKE IN THE TOP OF A CORNER FENCE POST

- 7) LESLIE M. GOULD, L.S. 142, ASSISTANT COUNTY ENGINEER AND COUNTY SURVEYOR FROM 1953 TO 1978, FOR W. D. KRETSINGER, P.E. 5150, COUNTY ENGINEER FROM 1952 TO 1981, IN SURVEY F36002 IN THE SURVEY FILE FOR TOWNSHIP 18, RANGE 12 FOR A *PLAT OF SURVEY* TO DETERMINE THE DIMENSIONS AND ESTABLISH THE CORNERS OF A 10 ACRE TRACT IN THE SOUTHWEST 1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12 DATED JUNE 27, 1972.

HE SHOWS ON HIS *PLAT OF SURVEY* A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12 ON THE TOWNSHIP LINE.

THERE WAS NO DESCRIPTION OF THE "**MONUMENT**" THAT HE FOUND OR THAT HE SET FOR THIS CORNER RECORDED ON THIS SURVEY.

THERE ARE NO REFERENCE TIES TO THIS CORNER RECORDED ON THIS SURVEY.

- 8) LESLIE M. GOULD, L.S. 142, ASSISTANT COUNTY ENGINEER AND COUNTY SURVEYOR FROM 1953 TO 1978, FOR W. D. KRETSINGER, P.E. 5150, COUNTY ENGINEER FROM 1952 TO 1981, IN SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 18, RANGE 12 DATED APRIL 13, 1973, FOR A *PLAT OF SURVEY* TO DETERMINE THE DIMENSIONS AND ESTABLISH THE CORNERS OF A 10 ACRE TRACT IN THE SOUTHWEST 1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12.

HE SHOWS ON HIS *PLAT OF SURVEY* A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12 ON THE TOWNSHIP LINE.

THERE WAS NO DESCRIPTION OF THE "**MONUMENT**" THAT HE FOUND OR THAT HE SET FOR THIS CORNER RECORDED ON THIS SURVEY.

THERE ARE NO REFERENCE TIES TO THIS CORNER RECORDED ON THIS SURVEY.

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 14, 2001, FOR HIS PROJECT NUMBER 00379-02, FOR THE SUBDIVISION OF SECTION 36, TOWNSHIP 18, RANGE 12, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 18, RANGE 12, SAID THAT HE DEEMED THAT THE SOUTH QUARTER CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12 ON THE TOWNSHIP LINE WAS **LOST**.

HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP FOR THE SOUTH QUARTER CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12 ON THE TOWNSHIP LINE ON THIS SURVEY.

HE SENT THE FOLLOWING **HORIZONTAL TIES:**

HIS **HORIZONTAL TIES** ARE ON PAGE 4

- 1) **2.54' EAST TO A 5/8" SQUARE REBAR FOUND**
- 2) 77.0' WEST TO A 1/2" REBAR WITH A CAP
- 3) 26.95' NNE TO A 40 D SPIKE AND WASHER IN A FENCE POST
- 4) 82.65' WNW TO A 40 D SPIKE AND WASHER IN A CORNER FENCE POST
- 5) 12.5' EAST TO A LINE OF HEDGE TO THE SOUTH EXTENDED
- 6) IN THE CENTERLINE OF THE TRAVELED WAY OF THE GRAVEL ROAD EAST AND WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 77.00' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR A TRACT CORNER
- 2) 1,319.62' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12
- 3) 2,639.24' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12
- 4) 2,638.28' EAST ON THE TOWNSHIP LINE TO THE 1" IRON PIN THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12 AT THE TOWNSHIP CORNER
- 5) 2,648.58' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP THAT HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12
- 6) 3,973.17' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR THE EAST 1/16TH CORNER OF THE NW1/4 OF SECT. 36, TOWNSHIP 18, RANGE 12
- 7) 5,297.76' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP THAT HE SET FOR THE NORTH QUARTER CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12

- 10) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 30, 2015, FOR HIS PROJECT NUMBER 15257-02, FOR THE SURVEY OF A 20.30 ACRE TRACT IN THE EAST HALF OF THE SOUTHWEST QUARTER OF SECTION 36, TOWNSHIP 18, RANGE 12 FOR EK REAL ESTATE, SURVEY F36004 IN THE SURVEY FILE FOR TOWNSHIP 18, RANGE 12.

HE SAID THAT HE FOUND THE EXISTING RECORD 5/8" IRON BAR WITH A LYON COUNTY CAP AT THE SOUTH QUARTER CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12 ON THE TOWNSHIP LINE FROM HIS EXISTING REFERENCE TIES IN 2001 FOR HIS PROJECT NUMBER 00379-02 ON FILE AT THE LYON COUNTY ENGINEERS OFFICE.

- 1) **2.54' EAST TO A 5/8" SQUARE REBAR FOUND [HORIZONTAL TIE]**
- 2) **77.0' WEST TO A 1/2" IRON BAR WITH HIS "PS 752 S. BROSEMER" CAP FOUND**
- 3) 27.00' NNE TO A BOLT AND WASHER IN A FENCE POST
- 4) 29.90' NE TO A BOLT AND WASHER IN A FENCE POST
- 5) 12.50' EAST TO THE LINE OF HEDGE TO THE SOUTH EXTENDED
- 6) IN THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 190 EAST AND WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 77.00' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE FOUND FROM A PREVIOUS SURVEY AT THE POINT OF BEGINNING FOR THE 20.30 ACRE TRACT
- 2) 125.00' WEST ON THE TOWNSHIP LINE TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP THAT HE SET FOR THE SOUTHWEST CORNER OF THE 20.30 ACRE TRACT
- 3) 1,319.59' WEST ON THE TOWNSHIP LINE TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP THAT HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12

CONTINUED PAGE 5

- 11) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2017 FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR WITH AN ORANGE CAP** AT THE NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE PER SURVEY REFERENCE REPORT 991527 AND PER CORNER TIE NOTES FILED BY STEVE BROSEMER, L.S. 752, FROM THE LYON COUNTY ENGINEER'S OFFICE.
HE SENT THE FOLLOWING **HORIZONTAL TIES:**
- 1) **THIS RECOVERY REPORT HAS BEEN GENERATED PER KANSAS STATE REQUIREMENTS. SURVEY PREPARED HEREWITH IS ONGOING AND PART OF A LARGE PROJECT AND THUS THIS MONUMENTS POSITION HAS NOT YET BEEN FINALIZED AS THE TRUE CORNER LOCATION. SUBSEQUENT RECORD WILL BE FILED UPON COMPLETION OF THE ENTIRE SURVEY.**
 - 2) 77.2' SOUTH 88°13' WEST TO A FOUND 1/2" REBAR WITH A DAMAGED CAP
 - 3) 83.2' NORTH 70°12' WEST TO A FOUND 40 D NAIL WITH WASHER IN AN 8" WOOD BRACE POST
 - 4) 27.2' NORTH 09°57' EAST TO THE FOUND FACE OF A RAILROAD TIE
 - 5) 37.9' SOUTH 49°23' EAST TO THE FOUND FACE OF A 10' WOOD BRACE POST
- 12) JOHN F. WATSON, P.S. 1587, OF JOHN F. WATSON AND COMPANY OF MIDLAND TEXAS, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 12, 2017 FOR HIS PROJECT NUMBER 16-0040, THE SURVEY FOR THE READING WIND FARM, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR WITH AN ORANGE CAP** AT THE NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE PER SURVEY REFERENCE REPORT 991527 AND PER CORNER TIE NOTES FILED BY STEVE BROSEMER, L.S. 752, FROM THE LYON COUNTY ENGINEER'S OFFICE.
HE SENT THE FOLLOWING **HORIZONTAL TIES:**
- 1) 77.2' SOUTH 88°13' WEST TO A FOUND 1/2" REBAR WITH A DAMAGED RED CAP
 - 2) 83.2' NORTH 70°12' WEST TO A FOUND 40 D NAIL WITH WASHER IN AN 8" WOOD BRACE POST
 - 3) 27.2' NORTH 09°57' EAST TO THE FOUND FACE OF A RAILROAD TIE
 - 4) 37.9' SOUTH 49°23' EAST TO THE FOUND FACE OF A 10' WOOD BRACE POST
- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 22, 2020 FOR HIS PROJECT NUMBER 20146-02, FOR THE SURVEY ESTABLISHING THE EAST LINE OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12 FOR WILLEY, SURVEY F36006 IN THE SURVEY FILE FOR TOWNSHIP 18, RANGE 12, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" IRON BAR WITH A LYON COUNTY CAP** AT THE SOUTH QUARTER CORNER OF SECTION 36, TOWNSHIP 18, RANGE 12 ON THE TOWNSHIP LINE FROM HIS EXISTING REFERENCE TIES DATED OCTOBER 2015.
- 1) **77.00' WEST TO A 1/2" REBAR WITH HIS "PS 752 S. BROSEMER" CAP THAT HE FOUND**
 - 2) 27.00' NNE TO A BOLT AND WASHER IN A FENCE POST
 - 3) 12.50' EAST TO A LINE OF HEDGE TO THE SOUTH EXTENDED
 - 4) IN THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 190 EAST AND WEST
 - 5) 29.90' NE TO A BOLT AND WASHER IN A FENCE POST
 - 6) **2.54' EAST TO A 5/8" SQUARE REBAR FOUND [HORIZONTAL TIE]**
- HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,324.50' NORTH TO THE POSITION DETERMINED, NOT MONUMENTED FOR THE SOUTHWEST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12

- 2) 2,448.50' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP THAT HE FOUND FROM REFERENCE TIES AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12
 - 3) 1,319.25' EAST ON THE TOWNSHIP LINE TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP THAT HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12
 - 4) 2,638.50' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH "CLS WATSON" CAP THAT HE FOUND FROM REFERENCE TIES AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 36, TOWNSHIP 18, RANGE 12 AT THE TOWNSHIP CORNER
- 14) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, FOR HIS PROJECT NUMBER 20233-02, FOR THE SURVEY OF THE EAST HALF OF THE FRACTIONAL NORTHWEST QUARTER AND THE WEST 10.5 FEET OF THE WEST HALF OF THE FRACTIONAL NORTHEAST QUARTER OF SECTION 1, TOWNSHIP 19, RANGE 12 FOR JANICE HUME, SURVEY F01003 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12 DATED NOVEMBER 9, 2020, SHOWS ON HIS *PLAT OF SURVEY* THAT **HE FOUND THE 5/8" REBAR FROM HIS PROJECT NUMBER 20146** AT THE NORTHWEST CORNER OF THE FRACTIONAL NORTHEAST QUARTER OF SECTION 1, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE.
- HIS REFERENCE TIES FOR HIS PROJECT NUMBER 20146 DATED JUNE 22, 2020 ARE STILL VALID FOR THIS SURVEY.
- HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) 1,319.66' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR THAT HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE FRACTIONAL NW1/4 OF SECTION 1, TOWNSHIP 19, RANGE 12
 - 2) 1,319.25' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "PS 752" CAP THAT HE FOUND FROM HIS PROJECT NUMBER 20146 AT THE NORTHEAST CORNER OF THE E1/2 OF THE FRACTIONAL NE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 12
 - 3) 2,560.96' SOUTH TO THE 1/2" X 24" REBAR WITH A LYON COUNTY CAP THAT HE SET FOR THE SOUTHWEST CORNER OF THE W1/2 OF THE FRACTIONAL NE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 12
 - 4) 5,297.49' SOUTH TO THE 4" X 12" LIMESTONE THAT HE FOUND FROM HIS PROJECT NUMBER 20170 AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 1, TOWNSHIP 19, RANGE 12

NORTH QUARTER CORNER SECTION 01-19-12