

WEST 1/4 CORNER SECTION 06, TOWNSHIP 19 SOUTH, RANGE 12 EAST

1) ON PAGE 66 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A POST** AT THE WEST 1/4 CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 8, 1856, FROM WHICH:

- 1) AN ELM TREE 40" IN DIAMETER BEARS SOUTH 1° WEST AT 158 LINKS DISTANCE
- 2) AN ELM TREE 15" IN DIAMETER BEARS SOUTH 22° EAST AT 213 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 36" X 12" X 6" LIMESTONE THAT THEY SET FOR THE CORNER TO TOWNSHIPS 18 AND 19 SOUTH, RANGES 11 AND 12 EAST AT THE NORTHWEST CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12
- 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 17" X 3" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 6 AND 7, TOWNSHIP 19, RANGE 12

2) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 43 [PACKET 154 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] ROAD ON THE RANGE LINE BETWEEN RANGES 11 AND 12 THAT WAS SURVEYED ON OCTOBER 27, 1863 AND ESTABLISHED IN THE COMMISSIONERS JOURNAL ON PAGE 60, SHOWS ON HIS *PLAT OF SURVEY* THAT THIS ROAD PASSES OVER THE EAST QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE ON THIS ROAD SURVEY FOR A 40-FOOT-WIDE ROAD. HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO **LIMESTONE**.

HIS SURVEY NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) BEGINNING AT THE NORTHEAST CORNER OF SECTION 25, TOWNSHIP 19, RANGE 11;
- 2) THENCE NORTH ON THE RANGE LINE TO THE SOUTH BANK OF THE NEOSHO RIVER 3 MILES AND 33.70 CHAINS;
- 3) THENCE NORTH 76° WEST TO THE EDGE OF WATER ~~5.45~~ **3.45*** CHAINS;
- 4) THENCE NORTH 29° WEST 2.00 CHAINS TO NORTH BANK OF SAID RIVER;
- 5) THENCE NORTH 42° EAST 4.50 CHAINS TO THE SECTION LINE;
- 6) THENCE NORTH ON SAID SECTION LINE 2 MILES AND 48.62 CHAINS TO INTERSECT THE *EMPORIA AND LAWRENCE ROAD*
- 7) VIEWED AND SURVEYED OCTOBER 27, 1863. T. P. HALL, G. I. HUMPHREY AND O. M. SUTHERLAND, VIEWERS.
- 8) THE ABOVE LOCATION AND ESTABLISHED 40 FEET WIDE BY THE BOARD.
- 9) ***NOTE IN THE LEFT MARGIN OF PAGE 43:** 5.45 CHAINS CHANGED TO **3.45** CHAINS BY ORDER OF THE BOARD OF COUNTY COMMISSIONERS JANUARY 5, 1875. COMMISSIONERS RECORD PAGE 60

3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 68 RECORDED IN SURVEY BOOK "A" ON PAGE 168 FOR THE SURVEY OF LAND CONTAINED IN SECTION 1, TOWNSHIP 19, RANGE 11, FOR LAND OWNED BY MRS. RINKER, TO ESTABLISH THE CENTER CORNER, AND TO SURVEY 10 ACRES, MORE OR LESS, ON THE NORTHERN BOUNDARY OF THE WEST 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 1, TOWNSHIP 19, RANGE 11, THAT HE SURVEYED ON AUGUST 25 AND 26, 1868, SAID THAT **HE FOUND** THE EAST 1/4 CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE ON THIS SURVEY. HE DID NOT IDENTIFY THE MONUMENT THAT HE FOUND AT THIS CORNER ON THIS SURVEY, BUT THE MONUMENT OF RECORD FOR THIS CORNER WAS A **POST** THAT WAS SET BY THE GLO SURVEYORS.

HE USED THIS CORNER TO ESTABLISH THE CENTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12. HE NOTED THAT *NO PLAT OF SURVEY* WAS REQUIRED FOR THIS SURVEY.

HIS FIELD NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 322 RODS, 11 LINKS WEST TO THE FOUND WEST 1/4 CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11

- 4) S. K. McCRARY, DEPUTY COUNTY SURVEYOR FOR ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 TO 1906, IN SURVEY NUMBER 124, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 205 FOR L. S. NEWTON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF 60 ACRES OFF THE EAST SIDE AND 60 ACRES OFF THE WEST SIDE OF THE SOUTHEAST 1/4 OF SECTION ONE (1), TOWNSHIP NINETEEN (19), RANGE ELEVEN (11) AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, THAT HE SURVEYED ON MAY 1, 1905, SAID THAT **HE ESTABLISHED** THE PERMANENT NORTHEAST CORNER OF THE SOUTHEAST 1/4 CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE FROM AN ELM TREE 36" IN DIAMETER AT S. 22° E. AT 2.13 CHAINS DISTANCE, ON WHICH HE FOUND MARKS OF THE GOVERNMENT WITNESS TREE AS GIVEN IN THE FIELD NOTES FOR THIS CORNER.

HE SET A STONE FOR THE PERMANENT NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE ON LINE WITH A HEDGE EAST AND A WIRE FENCE RUNNING WEST FROM THE WITNESS TREES. HE DID NOT DESCRIBE THE STONE THAT HE SET FOR THIS CORNER ON THIS PERMANENT SURVEY, AND THERE WERE NO ADDITIONAL REFERENCE TIES TO THIS STONE ON THIS PERMANENT SURVEY.

HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 174 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 173" IN MISCELLANEOUS DRAWER NUMBER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE. [**NOTE:** SEE THE SURVEY AS HIS SURVEY NOTES AND HIS DRAWING DO NOT SHOW THE SAME CHAINING NUMBERS! WARREN CHIP WOODS, L. S. 603, LYON COUNTY SURVEYOR]

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 14.99 CHAINS WEST TO THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE EAST 60 ACRES OF THE SE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11
- 2) 19.98-1/4 CHAINS WEST TO THE STONE THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11
- 3) 25.98 CHAINS WEST TO THE STONE THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE WEST 60 ACRES OF THE SE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11
- 4) 39.98 CHAINS WEST TO THE STONE MARKED "1/4" THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11, FROM WHICH A 10" OAK TREE BEARS 5 LINKS EAST, AND A 5" OAK TREE BEARS 9 LINKS SOUTH AND 2 LINKS EAST
- 5) 59.97 CHAINS WEST TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11 AT 1 LINK WEST OF A BURR OAK TREE [**NOTE:** THIS SHOULD BE THE SOUTHWEST CORNER OF THE E1/2 OF THE NORTHWEST 1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11. WARREN CHIP WOODS, L.S 603, LYON COUNTY SURVEYOR]
- 6) 79.96 CHAINS WEST TO THE STONE THAT HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11, FROM WHICH A 12" WALNUT TREE BEARS 41 LINKS EAST AND 5 LINKS SOUTH, AND A COFFEE BEAN TREE BEARS NORTHWEST AT 45 LINKS

CONTINUED PAGE 3

- 5) R. W. BALL, COUNTY ENGINEER FROM 1949 TO 1952, FOR A *PLAT OF SURVEY* OF THE SOUTHWEST 1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11 DATED APRIL AND MAY 1951, SURVEY SR #01001 IN THE LARGE SURVEY DRAWER FOR SECTIONS 1 TO 8 IN TOWNSHIP 19, RANGE 11, SHOWS ON HIS SURVEY DRAWING A “**MARK**” FOR THE EAST 1/4 CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE.

HE DID NOT INDICATE IF HE FOUND OR IF HE SET A MONUMENT FOR THE EAST 1/4 CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THIS SURVEY, AND THERE ARE NO REFERENCE TIES TO THIS “MARK” AT THIS CORNER ON THIS SURVEY OR IN THE KRETSINGER COLLECTION OF REFERENCE TIE BOOKS FOR THIS TOWNSHIP.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640’ NORTH ON THE RANGE LINE “BY GOVERNMENT NOTES” TO A POINT IN THE CENTERLINE OF THE ROAD AT THE NORTHEAST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE TOWNSHIP LINE – NOT DESCRIBED
- 2) 2,640’ SOUTH ON THE RANGE LINE “BY GOVERNMENT NOTES” TO A POINT ON THE SOUTH SHOULDER OF THE ROAD FOR THE SOUTHEAST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 – NOT DESCRIBED

- 6) IN A *REPORT OF SURVEY* FOR SURVEY F01004 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 11 WITH NO NAME OR DATE, THE SURVEYOR SAID THAT “HE SET A POINT” FOR THE EAST 1/4 CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE BY RUNNING A LINE NORTH FROM THE “SECTION CORNER IN PAVEMENT” AT THE SOUTHEAST CORNER OF SECTION 12, TOWNSHIP 19, RANGE 11. THE SURVEYOR DID NOT SIGN THE REPORT, HE DOES NOT DESCRIBE THE “MONUMENT” THAT HE SET FOR THIS “POINT”, AND THERE ARE NO REFERENCE TIES TO THIS “POINT” ON THIS SURVEY OR IN THE KRETSINGER COLLECTION OF REFERENCE TIE BOOKS FOR THIS TOWNSHIP.

- 7) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 30, 1985, FOR HIS PROJECT NUMBER 85031, FOR THE SURVEY OF A 15 ACRE TRACT, MORE OR LESS, LOCATED IN THE NORTHEAST QUARTER OF SECTION 1, TOWNSHIP 19, RANGE 11, AND RECORDED IN VOLUME 415 ON PAGE 411 IN THE REGISTER OF DEEDS OFFICE ON APRIL 17, 1985, SURVEY F01003 IN THE SURVEY FILE FOR SECTIONS 1 TO 8 IN TOWNSHIP 19, RANGE 11, SAID THAT **HE RESET** THE EAST QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE.

IN HIS *REPORT OF SURVEY*, HE SAID THAT HE DUG IN THE ROAD CUT FOR THE STONE THAT WAS SET BY McCRARY IN HIS 1905 PERMANENT SURVEY FROM WITNESS TREES, BUT HE DID **NOT** FIND THE STONE OR ANY OTHER MONUMENT AT THE EAST 1/4 CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11.

HE SAID THAT McCRARY’S NOTES [BOTH ORIGINAL AND RECORD] STATE THAT THE CORNER FELL IN LINE WITH ‘FENCES AND HEDGE’ EAST AND WEST. DUE TO THE NON-ORIGINALITY OF THE CORNERS TO THE NORTH AND SOUTH, HE CONCLUDED THAT THE BEST EVIDENCE OF THE RECORD CORNER’S LOCATION WAS IN LINE WITH AN OLD FENCE TO THE EAST AND THE REMAINS OF THE FENCE TO THE WEST, AND 20 FEET WEST OF THE CORNER POST [40 FOOT SECTION LINE ROAD].

HE SET A 1/2” X 24” REBAR WITH HIS “LS 752” CAP FOR THE EAST QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE.

- 1) 20.0’ EAST TO A CORNER FENCE POST
- 2) IN LINE WITH THE REMAINS OF A FENCE TO THE EAST
- 3) 4.0’ EAST TO THE CENTERLINE OF THE TRAVELED WAY OF A TRAIL NORTH AND SOUTH
- 4) SEE THE REGISTER OF DEEDS FOR A RECORDED *REPORT OF SURVEY*

HIS *REPORT OF SURVEY* SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED PAGE 4

- 1) 2,639.5' SOUTH ON THE RANGE LINE TO AN UNVERIFIED 1/2" REBAR THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11
- 2) 2,642.4' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR THE NORTHEAST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE TOWNSHIP LINE

- 8) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 20, 1997, FOR HER PROJECT NUMBER 96282-02, FOR THE SUBDIVISION OF THE FRACTIONAL NORTHWEST QUARTER OF SECTION 6, TOWNSHIP 19, RANGE 12, SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12, SAID THAT **SHE FOUND THE EXISTING RECORD 1/2" REBAR WITH "LS 752" CAP** AT THE WEST QUARTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DATED APRIL 1985.

SHE NOTED ON HER SURVEY DRAWING THAT THIS SECTION CORNER IS ALSO THE SOUTHWEST CORNER OF THE 59.50 ACRE THOMAS TRACT.

- 1) 13.45' WSW TO A NAIL AND WASHER IN A TRIPLE HACKBERRY TREE
- 2) 21.45' ENE TO A NAIL AND WASHER IN A TWIN MAPLE TREE
- 3) 22.15' SE TO A NAIL AND WASHER IN AN ELM TREE
- 4) 28.40' SW TO A NAIL AND WASHER IN THE NORTHEAST TRUNK OF A MULTIPLE BOX ELDER TREE
- 5) 6.9' WEST TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD TO THE NORTH

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,642.34' NORTH ON THE RANGE LINE TO THE #4 REBAR THAT SHE FOUND AT THE NORTHWEST CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE, BEING THE NORTHWEST CORNER OF THE 59.50 ACRE THOMAS TRACT
- 2) 2,639.49' SOUTH ON THE RANGE LINE TO THE IRON REBAR THAT SHE FOUND OVER THE EXISTING STONE PER RECORD AT THE SOUTHWEST CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12
- 3) 973.97' EAST TO THE #5 REBAR WITH A LYON COUNTY CAP THAT SHE SET FOR THE SOUTHEAST CORNER OF THE 59.50 ACRE THOMAS TRACT
- 4) 2,495.24' EAST TO THE #5 REBAR WITH LYON COUNTY CAP THAT SHE SET FOR THE CENTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12, BEING THE SOUTHEAST CORNER OF THE 90.08 ACRE JACOB TRACT
- 5) 5,219.04' EAST TO THE STONE THAT SHE FOUND AND MONUMENTED WITH A REBAR AND HER "LS 1130" CAP AT THE EAST 1/4 CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12

- 9) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 13, 1997, FOR HER PROJECT NUMBER 96283-02, FOR THE SURVEY OF A 12.97 ACRE TRACT AROUND AN EXISTING HOMESTEAD IN THE FRACTIONAL NORTHWEST QUARTER OF SECTION 6, TOWNSHIP 19, RANGE 12 FOR MRS. THOMAS, SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12, SAID THAT **SHE FOUND THE EXISTING RECORD 1/2" REBAR WITH THE "LS 752" CAP** AT THE WEST QUARTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE FROM HER EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED JANUARY 20, 1997.

SHE NOTED ON HER SURVEY DRAWING THAT THIS SECTION CORNER IS ALSO THE SOUTHWEST CORNER OF THE 46.53 ACRE TRACT.

- 1) 13.45' WSW TO A NAIL AND WASHER IN A TRIPLE HACKBERRY TREE
- 3) 21.45' ENE TO A NAIL AND WASHER IN A TWIN MAPLE TREE
- 4) 22.15' SE TO A NAIL AND WASHER IN AN ELM TREE

HER TIES ARE CONTINUED PAGE 5

- 5) 28.40' SW TO A NAIL AND WASHER IN THE NORTHEAST TRUNK OF A MULTIPLE BOX ELDER TREE
- 6) 6.9' WEST TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD TO THE NORTH

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 6) 2,642.34' NORTH ON THE RANGE LINE TO THE #4 REBAR THAT SHE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 6, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE, AND THE NORTHWEST CORNER OF THE 46.53 ACRE TRACT
- 7) 973.97' EAST TO THE #5 REBAR WITH A LYON COUNTY CAP THAT SHE SET FOR THE SOUTHEAST CORNER OF THE 46.53 ACRE TRACT
- 8) 2,495.24' EAST TO THE #5 REBAR WITH LYON COUNTY CAP THAT SHE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SEC. 6, TOWNSHIP 19, RANGE 12

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2009 FOR HIS PROJECT NUMBER 09055-02, FOR THE SURVEY OF THE WEST LINE OF A TRACT IN THE SOUTHEAST QUARTER OF SECTION 1, TOWNSHIP 19, RANGE 11 FOR KEITH KELLUM, SURVEY F01008 IN THE TOWNSHIP FILE FOR SECTIONS 1 TO 8 IN TOWNSHIP 19, RANGE 11, SAID THAT **HE FOUND THE EXISTING RECORD 1/2" REBAR WITH HIS "LS 752" CAP** AT THE EAST QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED APRIL 1985.

- 1) 13.45' WSW TO A NAIL AND WASHER IN A TRIPLE HACKBERRY TREE
- 2) 21.45' ENE TO A NAIL AND WASHER IN A TWIN MAPLE TREE
- 3) 22.15' SE TO A NAIL AND WASHER IN AN ELM TREE
- 4) 28.4' SW TO A NAIL AND WASHER IN A MULTIPLE BOX ELDER TREE
- 5) 6.9' WEST TO THE CENTERLINE OF THE TRAVELED WAY OF GRAVEL COUNTY ROAD "N" TO THE NORTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 988.20' WEST [988.68' PERMANENT SURVEY DISTANCE] TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR A TRACT CORNER
- 2) 2,646.08' WEST TO THE McCRARY PERMANENT SURVEY STONE THAT HE FOUND AT THE CENTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11
- 3) 2,639.30' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP THAT HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11

- 10) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 5, 2019 FOR HIS PROJECT NUMBER 19130-02 FOR THE SURVEY OF SEVEN TRACTS IN SECTION 1, TOWNSHIP 19, RANGE 11 FOR FULLER, SURVEY F01009 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 11, SAID THAT **HE FOUND THE EXISTING RECORD 1/2" REBAR WITH HIS "LS 752" CAP** AT THE EAST QUARTER CORNER OF SECTION 1, TOWNSHIP 19, RANGE 11 ON THE RANGE LINE FROM HIS EXISTING REFERENCE TIES ON FILE AT THE LYON COUNTY ROAD AND BRIDGE DEPARTMENT IN 2009 FOR HIS PROJECT NUMBER 09055-02.

- 1) 7' EAST TO THE TRAVELED WAY OF DIRT COUNTY ROAD "N" TO THE NORTH
- 2) 13.45' WSW TO A NAIL AND WASHER IN A TRIPLE HACKBERRY TREE
- 3) 22.15' SE TO A NAIL AND WASHER IN AN ELM TREE
- 4) 21.45' ENE TO A NAIL AND WASHER IN A MAPLE TREE

HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) 2,642.38' NORTH ON THE RANGE LINE TO THE 1/2" REBAR THAT HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11 AT THE TOWNSHIP CORNER

HIS INFORMATION IS CONTINUED PAGE 6

- 2) 2,639.65' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP THAT HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11
- 3) 1,322.90' WEST TO THE **LOCATION** FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11, BUT THE LOCATION WAS NOT MONUMENTED ON THIS SURVEY
- 4) 2,645.80' WEST TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11, BEING THE POINT OF BEGINNING FOR TRACT 3
- 5) 3,962.80' WEST TO THE **LOCATION** FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11, BUT THE LOCATION WAS NOT MONUMENTED ON THIS SURVEY
- 6) 5,285.02' WEST TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP THAT HE SET FOR THE SOUTHWEST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 1, TOWNSHIP 19, RANGE 11, BEING THE POINT OF BEGINNING FOR TRACT 2, TRACT 4 AND TRACT 5

WEST QUARTER CORNER SECTION 06-19-12