

NORTH 1/4 CORNER SECTION 07, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 543 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE QUARTER CORNER BETWEEN SECTIONS 6 AND 7, TOWNSHIP 19, RANGE 12 ON MARCH 12, 1857.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:

- 1) 37.25 CHAINS WEST TO THE 20" X 17" X 3" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 6 AND 7, TOWNSHIP 19, RANGE 12 ON THE WEST TOWNSHIP BOUNDARY.
- 2) 40.00 CHAINS EAST TO THE POST THAT THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 AND 8, TOWNSHIP 19, RANGE 12.
- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 11, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "A" ON PAGE 7 TO ESTABLISH THE CENTER POST OF SECTION 7, TOWNSHIP 19, RANGE 12, FOR DANIEL RICH AND DAVID MEDER, BOTH PARTIES BEING PRESENT, THAT HE SURVEYED ON JUNE 9, 1858.

HE SAID THAT **HE FOUND THE EXISTING NORTH QUARTER STONE POST** OF SECTION 7, TOWNSHIP 19, RANGE 12 ON THIS **PERMANENT SURVEY**.

HE DID NOT DESCRIBE THE **STONE POST** THAT HE FOUND AT THIS CORNER IN HIS FIELD NOTES ON THIS **PERMANENT SURVEY**, BUT THE STONE OF RECORD FOR THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 WAS THE **GLO LIMESTONE 24" X 12" X 3"**.

HE NOTED THAT THE ENTIRE LINE WAS IN LEVEL PRAIRIE.

NO *PLAT OF SURVEY* WAS RECORDED FOR THIS SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.86-1/2 CHAINS SOUTH TO THE STONE POST THAT HE SET FOR THE CENTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12.
- 2) 79.73 CHAINS SOUTH TO THE STONE THAT HE FOUND AT THE SOUTH QUARTER POST OF SECTION 7, TOWNSHIP 19, RANGE 12.
- 3) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 12 RECORDED IN SURVEY BOOK "A" ON PAGES 8 AND 9 FOR A **PERMANENT SURVEY** FOR DANIEL RICH AND DAVID MEDER TO PERMANENTLY ESTABLISH THE EAST AND WEST 1/4/4 POSTS, THE EAST AND WEST CENTER LINE, AND THE CENTER POST OF THE NORTHEAST 1/4 OF SECTION 7, TOWNSHIP 19, RANGE 12, THAT HE SURVEYED ON JUNE 17, 1858.

HE SAID THAT **HE FOUND THE EXISTING NORTH QUARTER STONE POST** OF SECTION 7, TOWNSHIP 19, RANGE 12 ON THIS **PERMANENT SURVEY**.

HE DID NOT DESCRIBE THE **STONE POST** THAT HE FOUND AT THIS CORNER IN HIS FIELD NOTES ON THIS **PERMANENT SURVEY**, BUT THE STONE OF RECORD FOR THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 WAS THE **GLO LIMESTONE 24" X 12" X 3"**.

HE NOTED THAT BOTH DANIEL RICH AND DAVID MEDER WERE PRESENT ON THIS SURVEY, AND THAT DAVID MEDER WAS THE ORIGINAL OWNER OF THE NORTHEAST 1/4 OF SECTION 7, TOWNSHIP 19, RANGE 12, AND DAVID RICH PURCHASED THE SOUTH HALF AND THE NORTHWEST 1/4 OF SAID 1/4 SECTION.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 19.93 CHAINS SOUTH TO THE STONE THAT HE SET FOR THE PERMANENT W1/4/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 7, TOWNSHIP 19, RANGE 12.
- 2) 39.86 CHAINS SOUTH TO THE STONE THAT HE FOUND AT THE CENTER POST OF SECTION 7, TOWNSHIP 19, RANGE 12.

CONTINUED PAGE 2

- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 37 RECORDED IN SURVEY BOOK "A" ON PAGE 133, FOR THE SURVEY OF A COUNTY ROAD PETITIONED BY RICKABAUGH AND OTHERS, THAT HE SURVEYED ON APRIL 14, 1868.

HE SAID THAT **HE SET A STONE IN THE GROUND** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 6, TOWNSHIP 19, RANGE 12 EAST OF THE 6TH P.M. DENOTING THE TERMINUS OF THIS ROAD SURVEY.

HE DID NOT DESCRIBE THE **STONE THAT HE SET IN THE GROUND** FOR THE SOUTH QUARTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 AT THE TERMINUS OF THIS ROAD SURVEY IN HIS FIELD NOTES.

HE DID NOT DESCRIBE IN HIS FIELD NOTES ANY OF THE ROAD STONES THAT HE SET ON THIS ROAD SURVEY.

HIS FIELD NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCED AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 2, TOWNSHIP 19, RANGE 11 EAST OF THE 6TH P.M. **AT A STONE SET IN THE GROUND**, FROM WHICH I WEST EAST VARIATION 9°00' EAST DISTANCE TO ANGLE 302 RODS; THENCE NORTH 47°00' EAST DISTANCE 18 RODS TO SECOND ANGLE, AT WHICH POINT SET 1 MILE STONE; FROM WHICH STONE I RUN SOUTH 47°00' EAST 23 RODS TO ANGLE, FROM WHICH I RUN EAST 319 RODS 18 LINKS TO THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 6, TOWNSHIP 19, RANGE 12 EAST OF THE 6TH P.M., AT WHICH POINT **SET A STONE IN THE GROUND** TO DENOTE THE TERMINUS OF THE ROAD.
- 2) THE ABOVE ROAD IS 2 MILES IN LENGTH, EXCEPTING 7 LINKS, AND 45 FEET IN WIDTH.

- 5) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 82 AND 83 (PACKET 159 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE) THAT WAS PETITIONED BY JOSEPH RICKABAUGH AND OTHERS THAT HE SURVEYED ON APRIL 15, 1868.

HE SAID THAT **HE SET A STONE IN THE GROUND** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 6, TOWNSHIP 19, RANGE 12 EAST OF THE 6TH P.M. DENOTING THE TERMINUS OF THIS ROAD SURVEY.

HE DID NOT DESCRIBE THE **STONE THAT HE SET IN THE GROUND** FOR THE SOUTH QUARTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 AT THE TERMINUS OF THIS ROAD SURVEY IN HIS FIELD NOTES.

HE DID NOT DESCRIBE IN HIS FIELD NOTES ANY OF THE ROAD STONES THAT HE SET ON THIS ROAD SURVEY.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCED AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 2, TOWNSHIP 19, RANGE 11 EAST OF THE 6TH P.M. **AT A STONE SET IN THE GROUND**, FROM WHICH I RUN EAST VARIATION 9°00' EAST DISTANCE TO ANGLE 302 RODS; THENCE NORTH 47°00' EAST DISTANCE 18 RODS TO SECOND ANGLE, AT WHICH POINT SET 1 MILE STONE; FROM WHICH STONE I RUN SOUTH 47°00' EAST 23 RODS TO ANGLE (THIS CALL WAS LEFT OUT IN THE DESCRIPTION IN ROAD RECORD BOOK "A"), FROM WHICH I RUN EAST 319 RODS 18 LINKS TO THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 6, TOWNSHIP 19, RANGE 12 EAST OF THE 6TH P.M., AT WHICH POINT **SET A STONE IN THE GROUND** TO DENOTE THE TERMINUS OF THE ROAD.
- 2) THE ABOVE ROAD IS 2 MILES IN LENGTH EXCEPTING 7 RODS.
- 3) THE ROAD IS 45 FEET IN WIDTH.
- 4) THIS ROAD SURVEY WAS FILED MAY 4, 1868.
- 5) THE ROAD WAS ESTABLISHED AND RECORDED ON JUNE 1, 1868, AND WAS SIGNED BY J. L. WILLIAMS, COUNTY CLERK.
- 6) A NOTE IN RED IN THE RIGHT MARGIN OF PAGE 83 STATES: **COMMISSIONER'S RECORD PAGE 215.**

CONTINUED PAGE 3

- 6) D. W. BOWMAN, DEPUTY COUNTY SURVEYOR FOR D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 47 RECORDED IN SURVEY BOOK "A" ON PAGE 143 FOR THE SURVEY OF LAND OWNED BY HILLERMAN, SMITH, LOGAN AND OTHERS, BEING SECTION 7, TOWNSHIP 19, RANGE 12, THAT HE SURVEYED ON MAY 4 AND 5, 1868.

HE SAID THAT **HE ESTABLISHED** THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 AT 160 RODS WEST OF THE NORTHEAST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12

HE SAID THAT HE ESTABLISHED THIS CORNER FROM THE WITNESS TREES GIVEN IN THE FIELD NOTES ON THIS SURVEY.

HE DID NOT DESCRIBE THE MONUMENT THAT **HE ESTABLISHED** FOR THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 IN HIS FIELD NOTES ON THIS SURVEY.

HE NOTED THAT NO *PLAT OF SURVEY* WAS REQUIRED FOR THIS SURVEY.

***** NOTE ON THE BOTTOM OF THE PAGE:** "THE ABOVE QUARTER CORNER ON THE NORTH BOUNDARY OF SECTION (7, TOWNSHIP 19, RANGE 12) NOT BEING ESTABLISHED WHERE THE GOVERNMENT CORNER FORMERLY STOOD, BY THE SWORN TESTIMONY OF JOHN AND MICHAEL WEAVER, ESTABLISHED IT PUTTING IT 2 RODS AND 1 LINK EAST AND 5 LINKS SOUTH OF WHERE IT WAS PLACED BY DEPUTY. CORRECTED THE CENTER CORNER BY PUTTING IT ON TRUE LINE THIS 29TH DAY OF NOVEMBER 1869. D. T. McAULEY, COUNTY SURVEYOR".

HE DID NOT DESCRIBE THE MONUMENT THAT HE RESET FOR THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 IN HIS FIELD NOTES ON THIS SURVEY.

HIS FIELD NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 160 RODS EAST TO THE NORTHEAST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 THAT HE ESTABLISHED FROM WITNESS TREES GIVEN IN THE FIELD NOTES.
 - 2) 149 RODS WEST TO THE FOUND NORTHWEST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE.
 - 3) 159 RODS, 59 LINKS SOUTH TO THE CENTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 THAT HE ESTABLISHED***
 - 4) 319 RODS, 18 LINKS SOUTH TO THE SOUTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 THAT HE ESTABLISHED.
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER THIRTY-SEVEN OF THE 6TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 37 TO PERMANENTLY ESTABLISH THE QUARTER CORNER BETWEEN SECTIONS 6 AND 7, TOWNSHIP 19, RANGE 12, THAT HE SURVEYED ON MAY 31, 1870.

HE SAID THAT HE RAN THE SECTION LINE FROM THE SOUTHEAST CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 WEST TO THE SOUTHWEST CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE. HE SAID THAT WHEN HE WENT TO RESET THIS QUARTER SECTION CORNER AT 2,640 FEET WEST OF THE SOUTHEAST CORNER, HE LISTED SIX PERSONS THAT OBJECTED TO THE LOCATION FOR THE SOUTH QUARTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12: JOHN WEAVER, DANIEL RICE, STILLMAN SMITH, MICHAEL WEAVER, RICHARD RICH, AND CHARLES WEAVER.

HE THEN ESTABLISHED THE CORNER AT 14 FEET EAST OF THE CORRECTED LOCATION, AND HE SAID THAT WHEN HE WAS DIGGING TO SET THE STONE, HE FOUND THE REMAINS OF AN OLD POST AT THIS LOCATION.

HE SET A STONE FOR THE PERMANENT QUARTER SECTION CORNER BETWEEN SECTIONS 6 AND 7, TOWNSHIP 19, RANGE 12 ON THE WEST SIDE OF THIS POST ON THIS PERMANENT SURVEY.

HIS INFORMATION IS CONTINUED PAGE 4

HE DID NOT DESCRIBE THE **STONE** THAT HE SET FOR THE PERMANENT NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 IN HIS FIELD NOTES ON THIS **PERMANENT SURVEY**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) 2,494' WEST TO THE FOUND CORNER TO SECTIONS 6 AND 7, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE.
- 2) 2,626' EAST TO THE FOUND CORNER TO SECTIONS 5, 6, 7 AND 8, TOWNSHIP 19, RANGE 12.

- 8) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 178 AND 179 PETITIONED BY IRA HINSHAW AND OTHERS FOR A ROAD IN TOWNSHIP 19, RANGE 12 THAT HE SURVEYED ON JULY 11, 1871.

HE SAID THAT **HE FOUND** THE QUARTER SECTION CORNER BETWEEN SECTIONS 6 AND 7, TOWNSHIP 19, RANGE 12 AT THE TERMINUS OF THIS ROAD SURVEY.

HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER AT THE TERMINUS OF THIS ROAD SURVEY IN HIS FIELD NOTES, BUT IN IN SURVEY NUMBER THIRTY-SEVEN OF THE 6TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 37 THAT HE SURVEYED ON MAY 31, 1870, HE HAD SET A **STONE** FOR THE PERMANENT NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE QUARTER SECTION CORNER BETWEEN SECTIONS 7 AND 18, TOWNSHIP 19, RANGE 12, AND RUNNING NORTH VARIATION 11°15' THROUGH SECTION 7 TO THE QUARTER SECTION CORNER BETWEEN SECTIONS 6 AND 7 (TOWNSHIP 19, RANGE 12) AT THE TERMINUS OF THIS ROAD SURVEY.
- 2) ONE MILE AND THREE (3) FEET.

THE VIEWERS COMMENTED: "WE ARE OF THE OPINION THAT THE SAID ROAD IS **NOT** REQUIRED BY THE COMMUNITY AS A PUBLIC HIGHWAY" THAT WAS FILED ON SEPTEMBER 4, 1871.

"THE FOREGOING ROAD WAS ESTABLISHED BY ORDER OF THE BOARD OF COUNTY COMMISSIONERS AT THE MEETING HELD OCTOBER 2, 1871. AND REFERENCE IS HEREBY MADE TO SAID ORDER IN THE RECORD OF SAID BOARD. FILED FOR RECORD OCTOBER 2, 1871" AND WAS SIGNED BY DAVID S. GILMORE, COUNTY CLERK.

A PENCIL NOTE ON THE BOTTOM OF PAGE 179 READS: "COURT **KILLED** THIS ROAD ON ACCOUNT OF LACK OF JURISDICTION ON PART OF THE COMMISSIONERS TO GRANT ROAD WHEN VIEWERS HAD REPORTED ADVERSELY".

- 9) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGES 238 AND 239 TO PERMANENTLY ESTABLISH THE NORTH 1/4 CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12, THAT HE SURVEYED ON JANUARY 26, 1880.

HE SAID THAT **HE SET A PERMANENT QUARTER SECTION CORNER** AT THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 ON THIS **PERMANENT SURVEY**.

HE DID NOT DESCRIBE THE MONUMENT THAT HE SET FOR THE PERMANENT NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 IN HIS FIELD NOTES ON THIS **PERMANENT SURVEY**.

HE NOTED THAT THIS PERMANENT QUARTER CORNER IS 28 FEET WEST OF A CORNER OR ROCK SET IN THE GROUND PLACED THERE BY ROBERT MILLIKEN, THEN COUNTY SURVEYOR.

ON PAGES 338 AND 339 IS THE TESTIMONY OF FIVE PERSONS THAT HE USED FOR EVIDENCE TO ESTABLISH THE **PERMANENT QUARTER CORNER** AT THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12.

HIS FIELD NOTES ARE AS FOLLOWS:

1) COMMENCING AT THE NORTHEAST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12, A STONE SET IN THE GROUND WITNESSED BY SEVERAL WITNESS TREES, I RAN NORTH 79°15' WEST ON A TRUE LINE 658 FEET THE NEOSHO RIVER COURSES SOUTH, 2,640 FEET SET A PERMANENT QUARTER SECTION CORNER 28 FEET WEST OF A CORNER OR ROCK SET IN THE GROUND PLACED THERE BY ROBERT MILLIKEN, THEN COUNTY SURVEYOR. AT 5,102 FEET THE NORTHWEST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 (ON THE RANGE LINE).

10) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 95, A ROAD SURVEY FOR W. B. MEYERS, PRINCIPAL PETITIONER, FOR A COUNTY ROAD IN SECTION 7, TOWNSHIP 19, RANGE 12 RECORDED IN SURVEY BOOK "F" ON PAGE 175 THAT HE SURVEYED ON JUNE 21, 1904.

HE SAID THAT **HE FOUND THE EXISTING NORTH QUARTER CORNER STONE AT 20 FEET WEST OF A FENCE AND 1 FOOT NORTH OF A FENCE EXTENDING EAST** AT THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 TO BEGIN THIS ROAD SURVEY.

HE DID NOT DESCRIBE THE **STONE** THAT HE FOUND AT THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 TO BEGIN THIS ROAD SURVEY IN HIS FIELD NOTES.

THERE WERE NO ADDITIONAL REFERENCE TIES TO THIS **STONE** RECORDED ON THIS ROAD SURVEY.

HE NOTED ON HIS *PLAT OF SURVEY* THAT THIS CORNER WAS THE NORTHWEST CORNER OF THE A. LIGGETT TRACT AND THE NORTHEAST CORNER OF THE J. O. PATTERSON TRACT.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

1) BEGINNING AT THE NORTH QUARTER CORNER **STONE** OF SECTION 7, TOWNSHIP 19, RANGE 12 AT 20 FEET WEST OF A FENCE AND 1 FOOT NORTH OF A FENCE EXTENDING EAST; THENCE RAN SOUTH ON THE QUARTER SECTION LINE 1 MILE TO THE **STONE** AT THE SOUTH QUARTER CORNER OF SAID SECTION 7, TOWNSHIP 19, RANGE 12 AT 31 FEET NORTH OF THE POST AT THE EAST END OF A GATE, AND THERE ENDING.

2) WIDTH OF ROAD 40 FEET, 20 FEET ON EACH SIDE OF LINE.

11) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 588 IN ROAD RECORD BOOK "D" ON PAGES 221 THROUGH 224 (PACKET 734 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE) THAT WAS PETITIONED BY W. B. MYERS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19, RANGE 12 THAT HE SURVEYED ON JUNE 21, 1904.

HE SAID THAT **HE FOUND THE EXISTING NORTH QUARTER CORNER STONE AT 20 FEET WEST OF A FENCE AND 1 FOOT NORTH OF A FENCE EXTENDING EAST** AT THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 TO BEGIN THIS ROAD SURVEY.

HE DID NOT DESCRIBE THE **STONE** THAT HE FOUND AT THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 TO BEGIN THIS ROAD SURVEY IN HIS FIELD NOTES.

THERE WERE NO ADDITIONAL REFERENCE TIES TO THIS **STONE** RECORDED ON THIS ROAD SURVEY.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

1) BEGINNING AT THE NORTH QUARTER CORNER **STONE** OF SECTION 7, TOWNSHIP 19, RANGE 12 AT 20 FEET WEST OF A FENCE AND 1 FOOT NORTH OF A FENCE EXTENDING EAST; THENCE RAN SOUTH ON THE QUARTER SECTION LINE 1 MILE TO THE **STONE** AT THE SOUTH QUARTER CORNER OF SAID SECTION 7, TOWNSHIP 19, RANGE 12 AT 31 FEET NORTH OF THE POST AT THE EAST END OF A GATE, AND THERE ENDING.

- 2) WIDTH OF ROAD 40 FEET, 20 FEET ON EACH SIDE OF LINE.
- 3) IN THE *VIEWER'S REPORT OF DAMAGES CLAIMED AND AWARDED*, THE VIEWERS SAID THAT AFTER CAREFUL DELIBERATION WE ARE OF THE OPINION THAT SAID ROAD IS PRACTICABLE AND A PUBLIC UTILITY AND RECOMMEND THAT IT BE GRANTED AS SURVEYED AND LOCATED, AND THAT IT SHALL BE ESTABLISHED AND OPENED 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE. THEY NOTED THAT THE MAJORITY OF THE SCHOOL BOARD WERE IN ATTENDANCE AT THE VIEW BUT PRESENTED NO CLAIM FOR DAMAGES.
- 4) THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS RECORDED ON PAGE 224 DATED THE 8TH DAY OF JULY 1904 DECLARED THAT ROAD NUMBER 588 BE DECLARED A PUBLIC HIGHWAY AND THAT THE TRUSTEE OF PIKE AND EMPORIA TOWNSHIP BE NOTIFIED TO CAUSE THE SAME TO BE OPENED FOR PUBLIC TRAVEL.
- 5) ROAD 588 WAS LOCATED AND ESTABLISHED AND RECORDED ON THE 25TH DAY OF THE ELEVENTH MONTH 1904 AND WAS SIGNED BY ALVA J. SMITH, COUNTY SURVEYOR.

- 12) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19, RANGE 12 SHOWS A **STONE MARKED "1/4"** AT THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12.

THERE IS NO DESCRIPTION OF THE **STONE MARKED "1/4"** THAT THEY FOUND AT THIS CORNER, AND THERE IS NO DATE RECORDED ON THIS ENTRY.

NOTE: SEE THE PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 9 BY LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR, DATED **APRIL AND MAY 1955** THAT SAID THAT HE FOUND A STONE **NEAR** THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12. WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR.

- 1) 23.5' EAST TO A CORNER FENCE POST
- 2) 27.3' NORTHEAST TO THE NORTH GATE POST
- 3) 30.8' NORTHEAST TO THE EAST GATE POST
- 4) 66.2' NORTH OF WEST TO A TELEPHONE POLE

- 13) LESLIE M. GOULD, L.S. 142, ASSISTANT COUNTY ENGINEER AND COUNTY SURVEYOR FROM 1953 TO 1978, FOR W. D. KRETSINGER, P.E. 5150, COUNTY ENGINEER FROM 1952 TO 1981, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 9 AT THE REQUEST OF JACK FOWLER TO LOCATE THE NORTHERN BOUNDARY OF A TRACT IN SECTION 8, TOWNSHIP 19, RANGE 12 FOR CAMP ALEXANDER.

HE SAID THAT **HE FOUND THE EXISTING STONE NEAR** THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 ON THIS **PERMANENT SURVEY**.

HE MEASURED 2,494.25 FEET WEST TO THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE, AND THEN MEASURED 23,636.5 FEET EAST TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 11, TOWNSHIP 19, RANGE 12. HE DETERMINED THAT THE STONE WAS TOO FAR TO THE EAST AND THAT IT SHOULD BE AT 2,643.5 FEET EAST OF THE NORTHWEST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 ACCORDING TO THE ORIGINAL CHAINING.

HE SAID THAT HE USED THE STONE FOR ALIGNMENT, BUT HE DID **NOT** USE THE STONE TO PROPORTION IN THE NORTHWEST CORNER OF SECTION 8, TOWNSHIP 19, RANGE 12.

THIS **PERMANENT SURVEY** BEGAN ON APRIL 6, 1955, AND WAS DELAYED DUE TO HIGH WATER AND AT ONE TIME DUE TO LACK OF COMPETENT HELP, AND WAS COMPLETED ON MAY 5, 1955.

HE DID NOT DESCRIBE THE STONE THAT HE FOUND **NEAR** THE NORTH QUARTER CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 IN HIS FIELD NOTES ON THIS **PERMANENT SURVEY**.

THERE ARE NO REFERENCE TIES TO THIS **STONE** RECORDED ON THIS **PERMANENT SURVEY**.

HIS FIELD NOTES AND *PLAT OF SURVEY* SHOWS THE FOLLOWING INFORMATION:

- 1) 2,654.18' EAST FROM THE STONE THAT HE FOUND TO THE 1-1/2" PIPE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 8, TOWNSHIP 19, RANGE 12.
- 2) 3,354.44' EAST TO THE 1-1/2" PIPE THAT HE SET FOR THE PERMANENT TRACT CORNER.

- 14) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 20, 1997, FOR HER PROJECT NUMBER 96282-02, FOR THE SUBDIVISION OF THE FRACTIONAL NORTHWEST QUARTER OF SECTION 6, TOWNSHIP 19, RANGE 12, SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12, SAID THAT **SHE FOUND THE EXISTING RECORD STONE THAT WAS SET BY COUNTY SURVEYOR ROBERT MILLIKEN** AT THE SOUTH QUARTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12.

SHE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP OVER THE STONE.

NOTE: SEE HER *REPORT OF SURVEY* FOR HER COMMENTS CONCERNING THIS **STONE** BASED ON THE MILLIKEN 1870 PERMANENT SURVEY.

- 1) 28.60' NORTH-NORTHWEST TO THE EAST FACE OF A STEEL GATE POST AT THE BOTTOM BOLT
- 2) 18.85' NORTHEAST TO THE SOUTH FACE OF A STEEL GATE POST AT THE BOTTOM BOLT
- 3) 41.70' SOUTHEAST TO A 1/2" REBAR SET IN THE SIDE SLOPE OF THE ROAD SHOULDER
- 4) 5.0' EAST TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD TO THE NORTH

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,494.65' WEST TO THE IRON REBAR THAT SHE FOUND OVER THE EXISTING STONE PER RECORD AT THE SOUTHWEST CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE.
- 2) 2,639.90' NORTH TO THE #5 REBAR WITH A LYON COUNTY CAP THAT SHE SET FOR THE CENTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12, BEING THE SOUTHEAST CORNER OF THE 90.08 ACRE JACOB TRACT.
- 3) 5,229.40' NORTH TO THE IRON REBAR THAT SHE FOUND OVER THE EXISTING STONE PER RECORD AT THE NORTH QUARTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE, BEING THE NORTHEAST CORNER OF THE 90.08 ACRE JACOB TRACT.

- 15) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 18, 2002, FOR HIS PROJECT NUMBER 21297-02, FOR THE SURVEY OF TRACTS IN SECTIONS 5 AND 6 IN TOWNSHIP 19, RANGE 12 FOR WAECHTER, SURVEYS F05005 AND F06006 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE** AT THE SOUTH QUARTER CORNER OF SECTION 6, TOWNSHIP 19, RANGE 12 FROM THE DISTANCES BY A PRIOR SURVEY BY DEPUTY COUNTY SURVEYOR POLLY JONES, L.S. 1130, IN 1997 FOR HER PROJECT NUMBER 96282-02 AND ON FILE AT THE LYON COUNTY ENGINEER'S OFFICE.

- 1) 3.00' EAST TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "N5" NORTH AND SOUTH

HIS INFORMATION IS CONTINUED PAGE 8

- 2) 5.00' SOUTH TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 180 TO THE WEST
- 3) 18.55' NORTHEAST TO THE NEAR FACE OF A PIPE GATE POST
- 4) 28.55' NORTHWEST TO THE NEAR FACE OF A PIPE GATE POST
- 5) **25.00' EAST TO A 1/2" REBAR WITH HIS "PS 752" CAP SET ON THIS SURVEY**

HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640.52' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP THAT HE FOUND AT THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 6, TOWNSHIP 19, RANGE 12.
- 2) 2,614.99' EAST TO THE 5/8" 24" REBAR WITH A LYON COUNTY CAP THAT **HE RESET** FOR THE SOUTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 6, TOWNSHIP 19, RANGE 12, BEING THE SOUTHWEST CORNER OF TRACT 1, THE POINT OF BEGINNING FOR TRACT 2, AND THE NORTHEAST CORNER OF TRACT 3.
- 3) 3,315.25' EAST TO THE 1-1/2" PIPE THAT HE FOUND (FROM A PREVIOUS PERMANENT SURVEY)
- 4) 5,244.95' EAST TO THE 1/2" REBAR THAT HE FOUND AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 5, TOWNSHIP 19, RANGE 12, BEING THE POINT OF BEGINNING FOR TRACT 1.

NORTH QUARTER CORNER 07-19-12