

NORTHWEST CORNER SECTION 10, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 527 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 15" X 3"** FOR THE CORNER TO SECTIONS 3, 4, 9 AND 10, TOWNSHIP 19, RANGE 12 ON FEBRUARY 26, 1857.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 20" X 14" X 2" LIMESTONE THAT THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 AND 4, TOWNSHIP 19, RANGE 12
 - 2) 77.85 CHAINS NORTH TO THE 28" X 10" X 2" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 3 AND 4, TOWNSHIP 19, RANGE 12 ON THE NORTH TOWNSHIP BOUNDARY
 - 3) 39.84 CHAINS EAST TO THE 19" X 16" X 4" LIMESTONE THAT THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 AND 10, TOWNSHIP 19, RANGE 12
 - 4) 79.68 CHAINS EAST TO THE 20" X 16" X 1-3/4" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 AND 11, TOWNSHIP 19, RANGE 12
 - 5) 40.00 CHAINS SOUTH TO THE 24" X 13" X 3" LIMESTONE THAT THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 9 AND 10, TOWNSHIP 19, RANGE 12
 - 6) 80.00 CHAINS SOUTH TO THE 24" X 11" X 2" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 AND 16, TOWNSHIP 19, RANGE 12
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY IN TOWNSHIP 19, RANGE 12 RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE OF PAGE 157 THAT HE SURVEYED ON MAY 23, 1878, SAID THAT **HE FOUND** THE SOUTHWEST CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12 ON THIS ROAD SURVEY. HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO **LIMESTONE**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE SOUTHEAST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12, I RAN WEST VARIATION 10°30' [ON THE SECTION LINE FOR] 5,280 FEET TO THE SOUTHWEST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12; THENCE WEST ON THE SECTION LINE VARIATION 10° [FOR] 5,280 FEET TO THE SOUTHWEST CORNER OF SECTION 2, TOWNSHIP 19, RANGE 12; THENCE WEST ON THE SECTION LINE VARIATION 10°45' [FOR] 5,280 FEET TO THE SOUTHWEST CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12; THENCE WEST ON THE SECTION LINE VARIATION 10°30' [FOR] 1,300 FEET TO THE FOREST HILL ROAD [AT THE TERMINUS OF THIS ROAD SURVEY]
 - 2) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 30 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 17 THROUGH 20 [PACKET 285 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY D. A. HUNTER AND OTHERS FOR A ROAD IN TOWNSHIP 19, RANGE 12 THAT HE SURVEYED ON MAY 23, 1878, WAS ESTABLISHED ON JULY 3, 1878 AS NOTED BY D. S. GILMORE, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK, AND RECORDED ON JANUARY 4, 1900 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE FOUND** THE SOUTHWEST CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12 ON THIS ROAD SURVEY. A NOTE ON THE PACKET COVER SAID TO SEE COMMISSIONERS RECORD 3 ON PAGE 47. HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO **LIMESTONE**.

HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED PAGE 2

- 1) BEGINNING AT THE SOUTHEAST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12, I RAN WEST VARIATION 10°30' 5,280 FEET TO THE SOUTHWEST CORNER OF SECTION 1, TOWNSHIP 19, RANGE 12, THENCE WEST ON THE SECTION LINE VARIANCE 10° 5,280 FEET TO THE SOUTHWEST CORNER OF SECTION 2, TOWNSHIP 19, RANGE 12; THENCE WEST ON THE SECTION LINE VARIATION 10°45' 5,280 FEET TO THE SOUTHWEST CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12; THENCE WEST ON THE SECTION LINE VARIATION 10°30' 1,300 FEET TO THE FOREST HILL AND AMERICUS ROAD AT THE TERMINUS OF THIS ROAD SURVEY.
 - 2) THE VIEWERS REPORTED IN FAVOR OF LOCATING SAID ROAD AS BEING NECESSARY FOR PUBLIC TRAVEL
 - 3) THE VIEWERS DETERMINED THAT IF SAID ROAD BE LOCATED THAT ITS WIDTH SHALL BE 40 (FORTY) FEET EXCEPTING THAT THE HEDGE FENCES ALONG THE NORTH LINE OF THE NW1/4 OF SECTION 11, TOWNSHIP 18, RANGE 12 SHALL BE HE NORTH AND SOUTH LINES OF SAID ROAD.
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE OF PAGE 216 THAT HE SURVEYED ON MARCH 26, 1881, FOR A COUNTY ROAD IN TOWNSHIPS 18 AND 19 IN RANGE 12 SAID THAT **HE FOUND** THE NORTHEAST CORNER OF SECTION 9, TOWNSHIP 19, RANGE 12 ON THIS ROAD SURVEY. HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO **LIMESTONE**.
HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) COMMENCING AT THE SOUTHEAST CORNER OF SECTION 9, TOWNSHIP 19, RANGE 12, I RAN NORTH 10°30' WEST 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 9, TOWNSHIP 19, RANGE 12; THENCE NORTH 10°45' WEST 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 4, TOWNSHIP 19, RANGE 12 [ON THE TOWNSHIP LINE]; THENCE NORTH 10°45' WEST 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 33, TOWNSHIP 19, RANGE 12; THENCE NORTH 10°15' WEST 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 28, TOWNSHIP 19, RANGE 12 [AT THE TERMINUS OF THIS ROAD SURVEY]
 - 2) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 110 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 26 TO 28 PETITIONED BY C. H. ELDRIDGE AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 18 AND 19 IN RANGE 12 [PACKET 356 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 26, 1881, WAS ESTABLISHED ON APRIL 16, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 5, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND** THE NORTHEAST CORNER OF SECTION 9, TOWNSHIP 19, RANGE 12 ON THIS ROAD SURVEY. HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER ON THIS ROAD SURVEY, BUT THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO **LIMESTONE**.
HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) COMMENCING AT THE SOUTHEAST CORNER OF SECTION 9, TOWNSHIP 19, RANGE 12, I RAN NORTH 10°30' WEST 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 9, TOWNSHIP 19, RANGE 12; THENCE NORTH 10°45' WEST 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 4. TOWNSHIP 19 RANGE 12 [ON THE TOWNSHIP LINE]; THENCE NORTH 10°45' WEST 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 33, TOWNSHIP 18, RANGE 12; THENCE NORTH 10°15' WEST 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 28, TOWNSHIP 18 RANGE 12 [AT THE TERMINUS OF THIS ROAD SURVEY]

- 2) THE VIEWERS WERE IN FAVOR OF LOCATING SAID ROAD AS BEING NECESSARY FOR PUBLIC TRAVEL
- 3) THE VIEWERS DETERMINED THAT IF SAID ROAD SHOULD BE LOCATED, ITS WIDTH SHALL BE SIXTY (60) FEET

6) MATTHEW BROWN, DEPUTY COUNTY SURVEYOR FOR R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER SEVENTY-ONE, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE SEVENTY-ONE THAT HE SURVEYED ON OCTOBER 9TH, 16 AND 17TH AND NOVEMBER 1ST, 1884 ORDERED BY N. J. WIRT TO SURVEY THE NORTHEAST 1/4 OF SECTION 4, TOWNSHIP 19, RANGE 12, SAID THAT **HE FOUND THE EXISTING STONE IN PLACE** AT THE SOUTHEAST CORNER OF SECTION 4, TOWNSHIP 19, RANGE 12 ON THIS **PERMANENT SURVEY**. HE DID NOT DESCRIBE ANY OF THE STONES THAT HE FOUND ON THIS PERMANENT SURVEY, BUT THE STONE OF RECORD FOR THE SOUTHEAST CORNER OF SECTION 4, TOWNSHIP 19, RANGE 12 WAS THE GLO LIMESTONE.

HE NOTED ON HIS *PLAT OF SURVEY* THAT THIS CORNER IS THE SOUTHEAST CORNER OF THE ELDRIDGE TRACT.

HIS FIELD NOTES AND *PLAT OF SURVEY* SHOWS THE FOLLOWING INFORMATION:

- 1) 2,619' WEST VARIATION 11° TO THE 2" X 8" X 11" STONE THAT HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 4, TOWNSHIP 19, RANGE 12 THAT "CORRESPONDS WITH FENCES", BEING THE SOUTHWEST CORNER OF THE ELDRIDGE TRACT AND THE SOUTHEAST CORNER OF THE W. B. SCOTT TRACT
- 2) 5,238' WEST VARIATION 11° TO THE TEMPORARY STAKE THAT HE SET FOR THE SOUTHWEST CORNER OF SECTION 4, TOWNSHIP 19, RANGE 12, BEING THE SOUTHWEST CORNER OF THE W. B. SCOTT TRACT
- 3) 2,640' NORTH VARIATION 10°36' TO THE STONE IN PLACE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 4, TOWNSHIP 19, RANGE 12, BEING THE NORTHEAST CORNER OF THE W. B. SCOTT TRACT AND THE SOUTHEAST CORNER OF THE N. J. WIRT TRACT
- 4) 5,138' NORTH VARIATION 10°36' TO THE 3" X 5" X 18" STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 4, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE, BEING THE NORTHEAST CORNER OF THE N. J. WIRT TRACT

7) LESLIE M. GOULD, L.S. 142, ASSISTANT COUNTY ENGINEER AND COUNTY SURVEYOR FROM 1953 TO 1978, FOR W. D. KRETSINGER, P.E. 5150, COUNTY ENGINEER FROM 1952 TO 1981, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 9 AT THE REQUEST OF JACK FOWLER TO LOCATE THE NORTHERN BOUNDARY OF A TRACT IN SECTION 8, TOWNSHIP 19, RANGE 12 FOR CAMP ALEXANDER, DOES **NOT** MENTION THE NORTHWEST CORNER OF SECTION 10, TOWNSHIP 19, RANGE 12 ON THIS **PERMANENT SURVEY**. HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE EAST TO THE STONE THAT HE FOUND IN PLACE AT THE NORTHEAST CORNER OF SECTION 11, TOWNSHIP 19, RANGE 12.

HE MAY HAVE DETERMINED A **CALCULATED LOCATION** FOR THE NORTHWEST CORNER OF SECTION 10, TOWNSHIP 19, RANGE 12 AS HE DOES GIVE A DISTANCE BETWEEN THE NORTHWEST AND NORTHEAST SECTION CORNERS. THE SURVEY BEGAN APRIL 6, 1955 AND WAS DELAYED DUE TO HIGH WATER AND AT ONE TIME DUE TO LACK OF COMPETENT HELP AND WAS COMPLETED ON MAY 5, 1955.

HIS *PLAT OF SURVEY* SHOWS THE FOLLOWING INFORMATION:

- 1) 5,248.37' WEST TO THE CALCULATED LOCATION FOR THE NORTHWEST CORNER OF SECTION 9, TOWNSHIP 19, RANGE 12

HIS INFORMATION IS CONTINUED PAGE 4

- 2) 7,219.73' WEST TO THE 1-1/2" PIPE THAT HE SET FOR A PERMANENT TRACT CORNER
 - 3) 10,519.99' WEST TO THE 1/2" PIPE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 8, TOWNSHIP 19, RANGE 12
 - 4) 13,134.57' WEST TO THE STONE THAT HE FOUND **NEAR** THE NORTH 1/4 CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12
 - 5) 15,628.82' WEST TO THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE
 - 6) 5,269.44' EAST TO THE CALCULATED LOCATION FOR THE NORTHEAST CORNER OF SECTION 10, TOWNSHIP 19, RANGE 12
 - 7) 10,501.87' EAST TO THE STONE THAT HE FOUND IN PLACE AT THE NORTHEAST CORNER OF SECTION 11, TOWNSHIP 19, RANGE 12
- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19, RANGE 12 SHOWS A **1/2" DIAMETER REBAR SET FOR THE REA** AT THE "SW CORNER SECTION 3, TOWNSHIP 19, RANGE 12", BUT THERE IS NO DATE ON THIS ENTRY. **[NOTE: VERIFY BEFORE USING AS THIS REBAR MAY HAVE BEEN "HEELED-IN" FOR UTILITY USE ONLY. WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR]**
- 1) 31.4' NW TO A CORNER FENCE POST
 - 2) 30.4' SW TO A CONNER FENCE POST
 - 3) 31.5' NE TO A CORNER FENCE POST
 - 4) 29.9' SW TO A CORNER FENCE POST
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19, RANGE 12 SHOWS AN **IRON PIN** AT THE "NE CORNER SECTION 9, TOWNSHIP 19, RANGE 12", BUT THERE IS NO DESCRIPTION OF THE "IRON PIN" THAT THEY FOUND OR SET FOR THIS CORNER, AND THERE IS NO DATE ON THIS ENTRY. **[NOTE: VERIFY BEFORE USING AT THIS "IRON PIN" MAY BE THE "REA PIN"!! WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR]**
- 1) 30.50' SE TO A SPIKE IN THE TOP OF A CORNER FENCE POST
 - 2) 33.10' NE TO A SPIKE IN THE TOP OF A CORNER FENCE POST
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 5, 1989, FOR HIS JOB NUMBER 89044, SAID THAT **HE FOUND AN EXISTING 1/2" REBAR** AT THE SOUTHWEST CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12.
- NOTE:** SEE SURVEY F03004 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12 FOR A COPY OF THE SURVEY MARKED *EXHIBIT A* THAT HE SUBMITTED ON AUGUST 8, 2019 IN SUPPORT OF TWO SURVEYS IN 2019. WARREN CHIP WOODS, P.S. 603, LYON COUNTY SURVEYOR
- 1) 20.0' NORTH TO A LINE OF FENCE TO THE WEST
 - 2) 22.0' NORTH TO A LINE OF FENCE TO THE EAST
 - 3) 23.0' WEST TO A LINE OF FENCE NORTH AND SOUTH
 - 4) 20.0' SOUTH TO A LINE OF FENCE EAST AND WEST
 - 5) 23.0' EAST TO A LINE OF FENCE TO THE SOUTH
 - 6) IN THE CENTERLINE OF THE TRAVELED WAY OF THE ROADS NORTH, SOUTH, EAST AND WEST
- HIS PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,642.30' NORTH TO THE 1/2" X 24" REBAR WITH HIS PLASTIC CAP THAT HE SET FOR THE WEST 1/4 CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12
 - 2) 5,143.63' NORTH TO THE 1/2" REBAR THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE
 - 3) 2,633.04' EAST TO THE 1/2" X 24" REBAR WITH HIS PLASTIC CAP THAT HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12

- 4) 3,949.55' EAST TO THE 1/2" X 24" REBAR WITH HIS PLASTIC CAP THAT HE SET FOR THE SOUTH 1/16TH CORNER OF THE SE1/4 OF SECTION 3, TOWNSHIP 19, RANGE 12
 - 5) 5,266.07' EAST TO THE 1/2" X 24" REBAR WITH HIS PLASTIC CAP THAT HE SET FOR THE SOUTHEAST CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12
- 11) STEVEN S. BROSEMER, P.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 2, 2019, FOR HIS PROJECT NUMBER 19166-02 FOR THE SURVEY OF THE LINE BETWEEN THE WEST-HALF OF THE EAST-HALF OF THE SOUTHWEST QUARTER (W1/2E1/2SW1/4) AND THE EAST-HALF OF THE EAST-HALF OF THE SOUTHWEST QUARTER (E1/2E1/2SW1/4) IN SECTION 3, TOWNSHIP 19, RANGE 12, SURVEY F03003 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12, SAID THAT **HE FOUND THE EXISTING RECORD 1/2" REBAR** AT THE SOUTHWEST CORNER OF SECTION 3, TOWNSHIP 19, RANGE 12 FROM HIS EXISTING REFERENCE TIES IN 1989 FOR HIS PROJECT NUMBER 89044-02 AND ON FILE AT THE LYON COUNTY ENGINEER'S OFFICE.
- 1) IN THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 180 EAST AND WEST
 - 2) IN THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "S" NORTH AND SOUTH
 - 3) 29.80' SW TO A CONCRETE NAIL AND BOTTLECAP IN A CORNER FENCE POST
 - 4) 31.10' NW TO A CONCRETE NAIL AND BOTTLECAP IN A CORNER FENCE POST
 - 5) 29.70' SE TO A CONCRETE NAIL AND BOTTLECAP IN A CORNER FENCE POST
 - 6) 35.30' NE TO A CONCRETE NAIL AND BOTTLECAP IN A CORNER FENCE POST
- HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) 2,642.62' NORTH TO THE 1/2" REBAR THAT HE FOUND FROM REFERENCE TIES AT THE NORTHWEST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 3, TOWNSHIP 19, RANGE 12
 - 2) 1,316.64' EAST TO THE *POSITION DETERMINED; NOT MONUMENTED* FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 3, TOWNSHIP 19, RANGE 12
 - 3) 1,974.96' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP THAT HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE E1/2 OF THE SW1/4 OF SECTION 9, TOWNSHIP 19, RANGE 12
 - 4) 2,633.28' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE FOUND FROM REFERENCE TIES AT THE SOUTHWEST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 3, TOWNSHIP 19, RANGE 12
 - 5) 3,949.96' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE FOUND FROM REFERENCE TIES AT THE SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 3, TOWNSHIP 19, RANGE 12

NORTHWEST CORNER 10-19-12