

NORTHWEST CORNER SECTION 32, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 534 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 28" X 14" X 2"** FOR THE CORNER TO SECTIONS 29, 30, 31 AND 32, TOWNSHIP 19, RANGE 12 ON MARCH 8, 1857.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH TO THE 21" X 12" X 2" LIMESTONE THAT THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 31 AND 32, TOWNSHIP 19, RANGE 12
 - 2) 80.00 CHAINS SOUTH TO THE 15" X 10" X 5" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 31 AND 32, TOWNSHIP 19, RANGE 12 ON THE SOUTH TOWNSHIP BOUNDARY
 - 3) 39.70-1/2 CHAINS EAST TO THE 19" X 13" X 4" LIMESTONE THAT THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 AND 32, TOWNSHIP 19, RANGE 12
 - 4) 79.41 CHAINS EAST TO THE 29" X 14" X 2" LIMESTONE THAT THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 AND 33, TOWNSHIP 19, RANGE 12
 - 5) 40.00 CHAINS WEST TO THE 24" X 15" X 2" LIMESTONE THAT THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 30 AND 31, TOWNSHIP 19, RANGE 12
 - 6) 78.94 CHAINS WEST TO THE POST THAT THEY SET FOR THE CORNER TO SECTIONS 30 AND 31, TOWNSHIP 19, RANGE 12 ON THE WEST TOWNSHIP BOUNDARY
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 110 RECORDED IN SURVEY BOOK "A" ON PAGE 201 FOR THE SURVEY OF A COUNTY ROAD PETITIONED BY W. H. PRIEST AND OTHERS IN TOWNSHIP 20, RANGE 13, TOWNSHIP 20, RANGE 12, AND TOWNSHIP 19, RANGE 11 FOR THE *HARTFORD TO EMPORIA ROAD* THAT HE SURVEYED ON APRIL 28 THROUGH MAY 1, 1869, INDICATES IN HIS FIELD NOTES THAT THIS ROAD PASSES OVER THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 19, RANGE 12, BUT HE DOES NOT CALL OUT THIS CORNER IN HIS FIELD NOTES. THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO LIMESTONE.

THERE WAS NO *PLAT OF SURVEY* RECORDED FOR THIS ROAD SURVEY. [NOTE: SEE THE *PLAT OF SURVEY* RECORDED IN ROAD RECORD BOOK "A" ON PAGE 132 FOR THE *PLAT OF SURVEY* FOR THIS ROAD. WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR]

HIS FIELD NOTES SHOW THE FOLLOWING INFORMATION:

- 1) BEGAN AT THE CENTER OF SECTION 15, TOWNSHIP 20, RANGE 13 EAST OF THE 6TH P.M. AT A **STONE SET IN THE GROUND**, FROM WHICH I RUN WEST VARIATION 11°30' EAST 476 RODS 13 LINKS; THENCE WEST 23°00' NORTH 365 RODS; THENCE WEST VARIATION 10°50' EAST 470 RODS; THENCE WEST 42°00' NORTH 445 RODS; THENCE WEST VARIATION 11°30' EAST 158 RODS; THENCE WEST 43°00' NORTH 444 RODS, 12 LINKS; THENCE WEST 11°00' EAST 96 RODS; THENCE NORTH 13°00' WEST 15 RODS; THENCE SOUTH 35°00' WEST 19 RODS; THENCE WEST VARIATION 11°30' EAST 363 RODS; THENCE NORTH 26°00' WEST 330 RODS; THENCE NORTH VARIATION 9°00' EAST 102 RODS; THENCE WEST 27°00' NORTH 28 RODS; THENCE NORTH 19°00' WEST 31 RODS; THENCE NORTH VARIATION 12°30' EAST 488 RODS; THENCE WEST TO RANGE LINE BETWEEN RANGES 11 AND 12 VARIATION 11°30' EAST; THENCE WEST VARIATION 10°15' EAST DISTANCE FROM LAST ANGLE 1,109 RODS; THENCE NORTH VARIATION 12°00' EAST 159 RODS TO THE SOUTH BOUNDARY OF EMPORIA TOWNSITE AT A **STONE SET IN THE GROUND**
- 2) LENGTH OF ROAD 15-1/2 MILES, 138 RODS AND 6 LINKS
- 3) THE WIDTH FROM THE BEGINNING TO THE SOUTHEAST CORNER OF SECTION 19, TOWNSHIP 19, RANGE 12 EAST OF THE 6TH P.M. TO BE 60 FEET, THENCE TO THE TERMINUS TO CONFORM TO THE WIDTH OF A ROAD ALREADY

ESTABLISHED, IT INTERSECTING A COUNTY ROAD AT THE ABOVE NAMED POINT

- 4) STONES WERE SET IN THE GROUND TO INDICATE THE VARIOUS MILES, ALSO AT THE BEGINNING AND ENDING OF THE ROAD

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 131 TO 134 [PACKET 261 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY W. H. PRIEST AND OTHERS FOR THE *HARTFORD TO EMPORIA ROAD* THAT WAS SURVEYED ON APRIL 29 AND 30 AND MAY 1, 1869, SHOWS ON HIS *PLAT OF SURVEY* THAT THIS ROAD PASSES OVER THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 19, RANGE 12, BUT HE DOES NOT CALL OUT THIS CORNER IN HIS FIELD NOTES. THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO **LIMESTONE**.
HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
 - 1) BEGAN AT THE CENTER OF SECTION 15, TOWNSHIP 20, RANGE 13 EAST OF THE 6TH P.M. AT A **STONE SET IN THE GROUND**, FROM WHICH I RUN WEST VARIATION 11°30' EAST 476 RODS 13 LINKS; THENCE WEST 23°00' NORTH 365 RODS; THENCE WEST VARIATION 10°50' EAST 470 RODS; THENCE WEST 42°00' NORTH 445 RODS; THENCE WEST VARIATION 11°30' EAST 158 RODS; THENCE WEST 43°00' NORTH 444 RODS, 12 LINKS; THENCE WEST 11°00' EAST 96 RODS; THENCE NORTH 13°00' WEST 15 RODS; THENCE SOUTH 35°00' WEST 19 RODS; THENCE WEST VARIATION 11°30' EAST 363 RODS; THENCE NORTH 26°00' WEST 330 RODS; THENCE NORTH VARIATION 9°00' EAST 102 RODS; THENCE WEST 27°00' NORTH 28 RODS; THENCE NORTH 19°00' WEST 31 RODS; THENCE NORTH VARIATION 12°30' EAST 488 RODS; THENCE WEST TO RANGE LINE BETWEEN RANGES 11 AND 12 VARIATION 11°30' EAST; THENCE WEST VARIATION 10°15' EAST DISTANCE FROM LAST ANGLE 1,109 RODS; THENCE NORTH VARIATION 12°00' EAST 159 RODS TO THE SOUTH BOUNDARY OF EMPORIA TOWNSITE AT A **STONE SET IN THE GROUND**
 - 2) LENGTH OF ROAD 15-1/2 MILES, 138 RODS AND 6 LINKS
 - 3) THE WIDTH FROM THE BEGINNING TO THE SOUTHEAST CORNER OF SECTION 19, TOWNSHIP 19, RANGE 12 EAST OF THE 6TH P.M. TO BE 60 FEET, THENCE TO THE TERMINUS TO CONFORM TO THE WIDTH OF A ROAD ALREADY ESTABLISHED, IT INTERSECTING A COUNTY ROAD AT THE ABOVE NAMED POINT
 - 4) STONES WERE SET (IN THE GROUND) TO INDICATE THE VARIOUS MILES, ALSO AT THE BEGINNING AND ENDING OF THE ROAD
 - 5) ESTABLISHED AS A PUBLIC HIGHWAY ON JULY 5TH, 1869, ACCORDING TO *PLAT AND SURVEY*. FILED AND RECORDED ON JULY 5TH, 1969 BY J. L. WILLIAMS, COUNTY CLERK
 - 6) A NOTE IN **RED** IN THE LEFT MARGIN OF PAGE 131 STATES: **COMMISSIONER'S RECORD PAGE 272**

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER THIRTY-NINE OF THE 6TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 39 THAT HE SURVEYED ON JUNE 4TH AND 6TH, 1870 TO ESTABLISH THE 1/4 CORNER BETWEEN SECTIONS 29 AND 30, TOWNSHIP 19, RANGE 12, THE 1/4 CORNER BETWEEN SECTION 19 AND 30, TOWNSHIP 19, RANGE 12, AND TO SET TEMPORARY 1/2/4 CORNERS AND THE CENTER CORNER ON THE NORTH AND SOUTH CENTER LINE OF SECTION 30, TOWNSHIP 19, RANGE 12, SAID THAT **HE FOUND** THE CORNER TO SECTIONS 29, 30, 32 AND 32, TOWNSHIP 19, RANGE 12 ON THIS **PERMANENT SURVEY**. HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER ON THIS PERMANENT SURVEY, BUT THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO **LIMESTONE**.

HIS INFORMATION IS CONTINUED PAGE 3

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,331' NORTH [1,331-1/4' CALCULATED] TO THE STONE THAT HE SET FOR THE PERMANENT 1/2/4 CORNER ON THE EAST SIDE OF THE SE1/4 OF SECTION 30, TOWNSHIP 19, RANGE 12
 - 2) 2,662' NORTH [2,662-1/2' CALCULATED] TO THE STONE THAT HE SET FOR THE PERMANENT 1/4 CORNER BETWEEN SECTIONS 29 AND 30, TOWNSHIP 19, RANGE 12
 - 3) 3,993' NORTH [3,993-3/4' CALCULATED] TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 30, TOWNSHIP 19, RANGE 12
 - 4) 5,324' NORTH [5,325' BY HIS NOTES] TO THE FOUND CORNER TO SECTIONS 19, 20, 29 AND 30, TOWNSHIP 19, RANGE 12
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 62 OF THE 7TH TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 210 [PACKET 39 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE] THAT HE SURVEYED ON JULY 15, 1872 FOR A COUNTY ROAD IN TOWNSHIP 19 IN RANGES 11 AND 12, SHOWS ON HIS *PLAT OF SURVEY* IN PACKET 39 THAT THIS ROAD PASSES OVER THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 19, RANGE 12 ON THIS ROAD SURVEY. THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO LIMESTONE.

THERE WAS NO *PLAT OF SURVEY* RECORDED ON THIS PAGE. SEE PACKET 39 FOR THE *PLAT OF SURVEY* FOR THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING DESCRIPTION OF THE ROAD:

- 1) BEGAN AT THE CORNER TO SECTIONS 28, 29, 32 AND 33 [TOWNSHIP 19, RANGE 12] AND RAN WEST ON THE SECTION LINE TO THE QUARTER CORNER BETWEEN SECTIONS 30 AND 31; THENCE WEST 19 RODS AND 3-1/2 FEET; THENCE SOUTH VARIANCE 11°15' EAST 200 FEET AND SET AN ANGLE STONE; THENCE SOUTH 75° WEST 980 FEET AND SET AN ANGLE STONE 262-1/2 (?) FEET OF THE 1/2/4 CORNER ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 31, TOWNSHIP 19, RANGE 12; THENCE SOUTH VARIANCE 11° 1,087-1/2 FEET AND SET AN ANGLE STONE; THENCE WEST ON 1/2 SECTION LINE TO THE SOUTHEAST CORNER OF LOT BELONGING TO SCHOOL DISTRICT NO. 49; THENCE SOUTH 53°35' WEST 330 FEET TO AN ANGLE STONE; THENCE NORTH 64° WEST 494 FEET TO AN ANGLE STONE ON LINE 452 FEET WEST OF THE 1/2/4 CORNER; THENCE WEST 864 FEET TO THE 1/4/4 CORNER IN THE NORTHWEST 1/4 OF SECTION 36, TOWNSHIP 19, RANGE 11; THENCE NORTH TO THE LINE BETWEEN SECTIONS 25 AND 36 AT THE 1/2/4 CORNER; THENCE WEST TO THE CORNER BETWEEN SECTIONS 25, 26, 35 AND 36; THENCE NORTH ON THE SECTION LINE TO THE 1/4 CORNER BETWEEN SECTIONS 25 AND 26; THENCE NORTH ON SAME LINE 2,222 FEET TO AN ANGLE STONE; THENCE NORTH 59°40' EAST 170 FEET TO AN ANGLE STONE; THENCE NORTH 9° EAST 110 FEET TO AN ANGLE STONE AT THE EDGE OF WATER; THENCE NORTH 17°45' WEST 90 FEET TO AN ANGLE STONE ACROSS THE RIVER; THENCE NORTH 72° WEST 238 FEET TO AN ANGLE STONE ON THE SECTION LINE 70 FEET NORTH OF THE CORNER TO SECTIONS 23, 24, 25 AND 26; THENCE NORTH ON SAID LINE 985 FEET TO INTERSECT THE COUNTY ROAD ON LINE BETWEEN SECTIONS 23 AND 24 [TOWNSHIP 19, RANGE 11 AT THE TERMINUS OF THIS ROAD SURVEY.
 - 2) NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 204 [PACKET 39 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY B. F. PARKER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19 IN RANGES 11 AND 12, THAT HE SURVEYED ON JULY 15, 1872, SHOWS ON HIS *PLAT OF SURVEY* IN PACKET 39 THAT THIS ROAD PASSES OVER THE NORTHWEST CORNER OF SECTION

32, TOWNSHIP 19, RANGE 12 ON THIS ROAD SURVEY. THE MONUMENT OF RECORD FOR THIS CORNER WAS THE GLO LIMESTONE.

THERE WERE NO FIELD NOTES OR *PLAT OF SURVEY* RECORDED ON PAGE 204. SEE PACKET 39 FOR THE FIELD NOTES AND *PLAT OF SURVEY* FOR THIS ROAD SURVEY.

HIS FIELD NOTES AND *PLAT OF SURVEY* IN PACKET 39 SHOWS THE FOLLOWING INFORMATION:

- 1) BEGINNING AT THE CORNER TO SECTIONS 28, 29, 32 AND 33 TOWNSHIP 19, RANGE 12 AND RUNNING WEST ON LINE BETWEEN SECTIONS 29 AND 32 AND 30 AND 32 499-1/4 RODS; THENCE SOUTH 12 RODS; THENCE SOUTH 75°20' WEST 65-9/10 RODS TO THE NORTH AND SOUTH CENTERLINE OF THE NORTHWEST 1/4 OF SECTION 31; THENCE SOUTH ON SAID LINE 69-1/3 RODS TO THE EAST AND WEST CENTERLINE OF SAID NORTHWEST 1/4 OF SECTION 31; THENCE WEST ON SAID LINE 219-42/100 RODS TO THE NORTHEAST CORNER OF SCHOOL HOUSE LOT NUMBER 49; THENCE SOUTH 53°35' WEST 20 RODS; THENCE NORTH 84° WEST 30 RODS TO THE EAST AND WEST CENTERLINE OF THE NORTHWEST 1/4 OF SECTION 36 TOWNSHIP 19 RANGE 11; THENCE WEST ON SAID LINE 52-6/10 RODS; THENCE NORTH 80 RODS TO THE LINE BETWEEN SECTIONS 25 AND 36 AT THE 1/2/4 CORNER; THENCE WEST ON SAID SECTION LINE TO THE CORNER TO SECTIONS 25, 26, 35 AND 36; THENCE NORTH ON LINE BETWEEN SECTIONS 25 AND 26, 294-2/3 RODS; THENCE NORTH 59°40' EAST 10-1/4 RODS; THENCE NORTH 9° EAST 6-6/10 RODS; THENCE NORTH 17°45' WEST 5-45/100 RODS CROSSING THE COTTONWOOD RIVER; THENCE NORTH 72° W. 14-42/100 RODS TO INTERSECT THE LINE BETWEEN SECTIONS 23 AND 24 AT 70 FEET NORTH OF THE CORNER TO SECTIONS 23, 24, 25 AND 26; THENCE NORTH ON SAID LINE 59-7/10 RODS INTERSECTING THE ROAD ALREADY ESTABLISHED [AT THE TERMINUS OF THIS ROAD SURVEY.
 - 2) TOTAL DISTANCE 4 MILES 240 RODS
 - 3) VIEWERS RECOMMENDED THAT THE ROAD ESTABLISHED AS A PUBLIC HIGHWAY AS LOCATED AND SURVEYED AND FURTHER RECOMMENDED THAT IT BE MADE FORTY FEET WIDE
 - 4) ORDERED ESTABLISHED AT A MEETING HELD BY THE COUNTY BOARD ON OCTOBER 7, 1872 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK
- 7) LESLIE M. GOULD, L.S. 142, ASSISTANT COUNTY ENGINEER AND COUNTY SURVEYOR FROM 1953 TO 1978, FOR W. D. KRETSINGER, P.E. 5150, COUNTY ENGINEER FROM 1952 TO 1981, IN SURVEY F29005 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12 ON AN AERIAL PHOTO SHOWING THE LOCATION OF THAT PART OF THE WEST 60 ACRES OF THE SOUTHWEST 1/4 OF SECTION 29, TOWNSHIP 19, RANGE 12 LYING SOUTH OF THE COTTONWOOD RIVER, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHWEST CORNER OF SECTION 29, TOWNSHIP 19, RANGE 12.
- THIS SURVEY IS NOT DATED, THERE IS NO DESCRIPTION OF THE "MONUMENT" THAT HE FOUND OR THAT HE SET FOR THIS CORNER ON THIS SURVEY, AND THERE ARE NO REFERENCE TIES TO THIS CORNER ON THIS SURVEY OR IN THE KRETSINGER REFERENCE TIE BOOKS FOR THIS TOWNSHIP.
- HIS SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) 894' EAST [DESCRIPTION STATES "984 FEET"] TO THE "MONUMENT" THAT HE SET FOR THE SOUTHEAST TRACT CORNER – NOT IDENTIFIED
 - 2) 1,475' NORTH TO THE IRON PIN THAT HE SET ON THE HIGH BANK OF THE COTTONWOOD RIVER
- 8) LESLIE M. GOULD, L.S. 142, ASSISTANT COUNTY ENGINEER AND COUNTY SURVEYOR FROM 1953 TO 1978, FOR W. D. KRETSINGER, P.E. 5150, COUNTY ENGINEER FROM 1952 TO 1981, IN SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12 TO SURVEY AND LOCATE THE BOUNDARIES OF A 1 ACRE

TRACT IN THE SOUTHEAST 1/4 OF SECTION 30, TOWNSHIP 19, RANGE 12, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF SECTION 30, TOWNSHIP 19, RANGE 12.

THIS SURVEY IS NOT DATED, THERE IS NO DESCRIPTION OF THE "MONUMENT" THAT HE FOUND OR THAT HE SET FOR THIS CORNER ON THIS SURVEY, AND THERE ARE NO REFERENCE TIES TO THIS CORNER ON THIS SURVEY OR IN THE KRETSINGER REFERENCE TIE BOOKS FOR THIS TOWNSHIP.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320' NORTH TO THE PIN THAT HE SET FOR THE SOUTHEAST CORNER OF THE 1 ACRE TRACT
- 2) 1,595' NORTH TO THE PIN ON THE BANK OF A SMALL CREEK FOR LINE

- 9) LESLIE M. GOULD, L.S. 142, ASSISTANT COUNTY ENGINEER AND COUNTY SURVEYOR FROM 1953 TO 1978, FOR W. D. KRETSINGER, P.E. 5150, COUNTY ENGINEER FROM 1952 TO 1981, IN SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12 TO LOCATE THE BOUNDARIES OF A 10 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 31, TOWNSHIP 19, RANGE 12 DATED MAY 7 AND 8, 1975, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE NORTHEAST CORNER OF SECTION 31, TOWNSHIP 19, RANGE 12.

THERE IS NO DESCRIPTION OF THE "IRON PIN" THAT HE FOUND OR THAT HE SET FOR THIS CORNER ON THIS SURVEY, AND THERE ARE NO REFERENCE TIES TO THIS "IRON PIN" ON THIS SURVEY OR IN THE KRETSINGER REFERENCE TIE BOOKS FOR THIS TOWNSHIP.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,273' WEST TO THE PIN THAT HE SET FOR THE NORTHWEST CORNER OF THE 10 ACRE TRACT
- 2) 342' SOUTH TO THE PIN THAT HE SET FOR THE SOUTHEAST CORNER OF THE 10 ACRE TRACT

- 10) WARREN CHIP WOODS, L.S.603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 11, 1991, **FOUND AN EXISTING OLD 1/2" IRON BAR AT 6" BELOW THE SURFACE OF GRAVEL COUNTY ROAD 150** AT THE SOUTHWEST CORNER OF SECTION CORNER OF SECTION 29, TOWNSHIP 19, RANGE 12 FROM RESEARCH IN THE COUNTY ENGINEER'S OFFICE.

I REPLACED THIS FOUND OLD 1/2" IRON BAR WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP FOR THE SOUTHWEST CORNER OF SECTION 29, TOWNSHIP 19, RANGE 12.

- 1) 35.6' NE TO A CONCRETE NAIL AND WASHER SET IN A CORNER FENCE POST
- 2) 37.2' SE TO A CONCRETE NAIL AND 2 WASHERS SET IN A CORNER FENCE POST
- 3) 33.6' SW TO A CONCRETE NAIL AND 3 WASHERS SET IN A CORNER FENCE POST
- 4) 31.2' NW TO A CONCRETE NAIL AND 4 WASHERS SET IN A CORNER FENCE POST
- 5) IN THE CENTERLINE OF THE TRAVELED WAY OF GRAVEL COUNTY ROAD "P" NORTH AND SOUTH
- 6) IN THE CENTERLINE OF THE TRAVELED WAY OF GRAVEL COUNTY ROAD 150 EAST AND WEST

- 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN **PERMANENT SURVEY NUMBER 65** RECORDED IN PERMANENT SURVEY BOOK 2 ORDERED BY THE BOARD OF COUNTY COMMISSIONERS OF LYON COUNTY TO LOCATE AND PERMANENTLY ESTABLISH THE WEST LINE OF THE SOUTHEAST 1/4 OF SECTION 30, TOWNSHIP 19, RANGE 12 AT THE REQUEST OF LLOYD AND SORIA FARR, FOR HIS JOB NUMBER 94178-02, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTHEAST CORNER OF SECTION 30, TOWNSHIP 19, RANGE 12 FROM THE EXISTING REFERENCE TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE ON THIS **PERMANENT SURVEY**.

THE FIELD WORK WAS CONDUCTED FROM JUNE 20 TO JULY 15, 1994; HE SIGNED IT ON OCTOBER 11, 1994; AND IT WAS FILED FOR RECORD ON NOVEMBER 14, 1994 BY WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR.

- 1) IN LINE WITH THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "P" NORTH AND SOUTH
- 2) IN LINE WITH THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 150 EAST AND WEST
- 3) 34.4' NE TO A NAIL AND FLAGGING IN A CORNER FENCE POST
- 4) 34.5' SE TO A TELEPHONE PEDESTAL

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640.46' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 30, TOWNSHIP 19, RANGE 12
- 2) 5,210.94' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 30, TOWNSHIP 19, RANGE 12 ON THE RANGE LINE
- 3) 2,663.97' NORTH TO THE GLO STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 30, TOWNSHIP 19, RANGE 12
- 4) 5,325.01' NORTH TO THE 1/2" REBAR THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 30, TOWNSHIP 19, RANGE 12, THAT HE SET IN 1988 TO REPLACE A CHARRED STAKE HE FOUND

- 12) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 29, 1994, FOR HIS JOB NUMBER 93-12-054, LARGE SURVEY SR #32001 IN THE SURVEY DRAWER FOR TOWNSHIP 19, RANGE 12, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTHWEST CORNER OF SECTION 32, TOWNSHIP 19, RANGE 12 PER SECTION CORNER REPORTS FILED AT THE COUNTY ENGINEER'S OFFICE.

[NOTE: SEE PERMANENT SURVEY NUMBER 65 RECORDED IN PERMANENT SURVEY BOOK 2 THAT WAS FILED NOVEMBER 14, 1994. WARREN CHIP WOODS, L.S. 603, LYON COUNTY SURVEYOR]

- 1) 32.6' SW TO A MASONRY NAIL IN A CORNER FENCE POST
- 2) 31.3' NW TO A MASONRY NAIL IN A CORNER FENCE POST
- 3) 34.3' NE TO A MASONRY NAIL IN A CORNER FENCE POST
- 4) 34.4' SE TO THE TOP CENTER OF A TELEPHONE RISER
- 5) IN THE CENTERLINE OF NORTH AND SOUTH GRAVEL COUNTY ROAD "P"
- 6) 1' SOUTH OF THE TRAVELED WAY OF EAST AND WEST COUNTY ROAD 150

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,630.92' EAST TO THE NORTH 1/4 CORNER OF SECTION 32, TOWNSHIP 19, RANGE 12
- 2) 5,252.05' EAST TO THE NORTHEAST CORNER OF SECTION 32, TOWNSHIP 19, RANGE 12
- 3) 2,652.26' SOUTH TO THE WEST 1/4 CORNER OF SECTION 32, TOWNSHIP 19, RANGE 12
- 4) 5,304.29' SOUTH TO THE SOUTHWEST CORNER OF SECTION 32, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE

- 13) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 3, 2019, FOR HIS PROJECT NUMBER 19232-02, FOR THE SURVEY OF THE SOUTHWEST QUARTER OF THE NORTHEAST QUARTER OF THE NORTHEAST QUARTER OF SECTION 31, TOWNSHIP 11, RANGE 12 FOR EK REAL ESTATE/ANDERSON, SURVEY F31002 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 12, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTHEAST CORNER OF SECTION 31, TOWNSHIP 19, RANGE 12 FROM THE EXISTING REFERENCE TIES ON FILE WITH THE LYON

COUNTY SURVEYOR'S OFFICE FROM BLACKBOURN, L.S. 1127 DATED NOVEMBER 1994.

- 1) 32.6' SOUTHWEST TO A MASONRY NAIL IN A CORNER FENCE POST
- 2) 34.3' NORTHEAST TO A MASONRY NAIL IN A CORNER FENCE POST
- 3) 34.4' SOUTHEAST TO THE TOP OF A TELEPHONE PEDESTAL
- 4) 31.8' NORTHWEST TO A BENT SPIKE IN A POWER POLE
- 5) 1.0' SOUTH TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 140 EAST AND WEST
- 6) 1.0' EAST TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "P" NORTH AND SOUTH

HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320.33' WEST TO THE CALCULATED POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 31, TOWNSHIP 19, RANGE 12
- 2) 2,640.66' WEST TO THE 1/2" REBAR THAT HE FOUND FROM RECORD TIES AT THE NORTHWEST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 31, TOWNSHIP 19, RANGE 12
- 3) 1,326.21' SOUTH TO THE CALCULATED POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 31, TOWNSHIP 19, RANGE 12
- 4) 2,652.42' SOUTH TO THE 1/2" REBAR THAT HE FOUND FROM RECORD TIES AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 31, TOWNSHIP 19, RANGE 12
- 5) 5,304.71' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT BOX THAT HE FOUND FROM RECORD TIES AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 31, TOWNSHIP 19, RANGE 12 ON THE TOWNSHIP LINE

NORTHWEST CORNER 32-19-12